

## EU safety data sheet

**Trade name:** Multi Multifunktionsölspray**Product no.:** L27**Current version :** 5.0.0, issued: 05.05.2021**Replaced version:** 4.1.0, issued: 24.02.2021**Region:** GB**SECTION 1: Identification of the substance/mixture and of the company/undertaking****1.1 Product identifier****Trade name****Multi Multifunktionsölspray****1.2 Relevant identified uses of the substance or mixture and uses advised against****Relevant identified uses of the substance or mixture**

product for corrosion protection and cleaning

**Uses advised against**

No data available.

**1.3 Details of the supplier of the safety data sheet****Address**

BBC Cellpack GmbH

Carl-Zeiss-Strasse 20

79761 Waldshut-Tiengen

Telephone no. +49 (0)7741 6007-0

Fax no. +49 (0)7741 64989

e-mail electrical.products@cellpack.com

**Information provided by / telephone**

+49 (0)7741 6007-0

**Advice on Safety Data Sheet**

msds@cellpack.com

**1.4 Emergency telephone number**

For medical advice (in German and English):

+49 (0)551 192 40 (Giftinformationszentrum Nord)

**SECTION 2: Hazards identification****2.1 Classification of the substance or mixture****Classification in accordance with Regulation (EC) No 1272/2008 (CLP)**

Aerosol 1; H222

Aquatic Chronic 3; H412

Asp. Tox. 1; H304

STOT SE 3; H336

**Classification information**

This product is assessed and classified using the methods and criteria below referred to in Article 9 of Regulation (EC) n° 1272/2008:

Physical hazards: determined through assessment data based on the methods or standards referred to in part 2 of Annex I to CLP

Health hazards and environmental hazards: determined through toxicological and ecotoxicological assessment data based on the methods or standards referred to in Part 3, 4 and 5 of Annex I to CLP.

**2.2 Label elements****Labelling according to Regulation (EC) No 1272/2008 (CLP Regulation)****Hazard pictograms**

GHS02



GHS07

**Signal word**

# EU safety data sheet

**Trade name:** Multi Multifunktionsölspray

**Product no.:** L27

**Current version :** 5.0.0, issued: 05.05.2021

**Replaced version:** 4.1.0, issued: 24.02.2021

**Region:** GB

Danger

**Hazardous component(s) to be indicated on label:**

Naphtha (petroleum), hydrotreated light

**Hazard statement(s)**

H222 Extremely flammable aerosol.  
H229 Pressurised container: May burst if heated.  
H336 May cause drowsiness or dizziness.  
H412 Harmful to aquatic life with long lasting effects.

**Hazard statements (EU)**

EUH066 Repeated exposure may cause skin dryness or cracking.

**Precautionary statement(s)**

P101 If medical advice is needed, have product container or label at hand.  
P102 Keep out of reach of children.  
P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.  
P211 Do not spray on an open flame or other ignition source.  
P251 Do not pierce or burn, even after use.  
P260 Do not breathe vapours/spray.  
P271 Use only outdoors or in a well-ventilated area.  
P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.  
P312 Call a POISON CENTER/doctor if you feel unwell.  
P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F.  
P501 Dispose of contents/container to a facility in accordance with local and national regulations.

**Supplemental label elements**

Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50 °C. Do not pierce or burn, even after use.

Keep out of the reach of children.

Regulation (EC) No 648/2004 on detergents (Annex VII):

>=30% aliphatic hydrocarbons

## 2.3 Other hazards

No data available.

## SECTION 3: Composition/information on ingredients

### 3.1 Substances

Not applicable. The product is not a substance.

### 3.2 Mixtures

**Chemical characterization**

Mixture of the following substances, containing non-hazardous substances:

**Hazardous ingredients**

No	Substance name	Additional information	
	CAS / EC / Index / REACH no	Classification (EC) 1272/2008 (CLP)	Concentration %
1	butane		
	106-97-8 203-448-7 601-004-00-0 -	Flam. Gas 1A; H220 Press. Gas; H280	>= 25.00 - < 50.00 wt%
2	Naphtha (petroleum), hydrotreated light		Contains < 0.1 % w/w benzene (EC No 200-753-7).
	64742-49-0 920-750-0 649-328-00-1	Flam. Liq. 2; H225 Asp. Tox. 1; H304 STOT SE 3; H336	>= 10.00 - < 25.00 wt%

# EU safety data sheet

**Trade name:** Multi Multifunktionsölspray

**Product no.:** L27

**Current version :** 5.0.0, issued: 05.05.2021

**Replaced version:** 4.1.0, issued: 24.02.2021

**Region:** GB

	01-2119473851-33	Aquatic Chronic 2; H411 EUH066		
3	<b>propane</b>			
	74-98-6 200-827-9 601-003-00-5 01-2119486944-21	Flam. Gas 1A; H220 Press. Gas liq.; H280	>= 10.00 - < 25.00	wt%
4	<b>isobutane</b>			
	75-28-5 200-857-2 601-004-00-0 01-2119485395-27	Flam. Gas 1A; H220 Press. Gas liq.; H280	< 5.00	wt%

Full Text for all H-phrases and EUH-phrases: pls. see section 16

No	Note	Specific concentration limits	M-factor (acute)	M-factor (chronic)
1	C, U	-	-	-
3	U	-	-	-
4	C, U	-	-	-

Full text for the notes: pls. see section 16 "Notes relating to the identification, classification and labelling of substances ((EC) No 1272/2008, Annex VI)".

## SECTION 4: First aid measures

### 4.1 Description of first aid measures

#### General information

In all cases of doubt, or when sickness symptoms persist, seek medical attention. Never give anything by mouth to an unconscious person. Remove soiled or soaked clothing immediately.

#### After inhalation

Remove to fresh air, keep patient warm and at rest. Irregular breathing/no breathing: artificial respiration. If unconscious place in recovery position and seek medical advice.

#### After skin contact

Wash skin thoroughly with soap and water or use recognised skin cleanser. Do NOT use solvents or thinners.

#### After eye contact

Remove contact lenses, irrigate copiously with clean, fresh water for at least 10 minutes, holding the eyelids apart and seek medical advice.

#### After ingestion

Do not induce vomiting. Call a doctor immediately. Never give anything by mouth to an unconscious person. Keep at rest.

### 4.2 Most important symptoms and effects, both acute and delayed

No data available.

### 4.3 Indication of any immediate medical attention and special treatment needed

No data available.

## SECTION 5: Firefighting measures

### 5.1 Extinguishing media

#### Suitable extinguishing media

Alcohol resistant foam, CO<sub>2</sub>, powders, water spray

#### Unsuitable extinguishing media

High power water jet

### 5.2 Special hazards arising from the substance or mixture

Fire will produce dense black smoke. Exposure to decomposition products may cause a health hazard. Exposure to heat may cause bursting of the aerosol packagings.

# EU safety data sheet

**Trade name:** Multi Multifunktionsölspray

**Product no.:** L27

**Current version :** 5.0.0, issued: 05.05.2021

**Replaced version:** 4.1.0, issued: 24.02.2021

**Region:** GB

## 5.3 Advice for firefighters

Cool endangered containers with water in case of fire. When extinguishing fires, use breathing apparatus with an independent source of air. DO NOT ALLOW RUN-OFF FROM FIRE FIGHTING TO ENTER DRAINS OR WATER COURSES

## SECTION 6: Accidental release measures

### 6.1 Personal precautions, protective equipment and emergency procedures

#### For non-emergency personnel

Exclude sources of ignition and ventilate the area. Do not inhale vapours. Refer to protective measures listed in sections 7 and 8.

#### For emergency responders

No data available. Personal protective equipment (PPE) - see Section 8.

### 6.2 Environmental precautions

Do not allow to enter drains. If the product contaminates lakes, rivers or sewage, inform appropriate authorities in accordance with local regulations.

### 6.3 Methods and material for containment and cleaning up

Contain and collect spillage with non-combustible absorbent materials, e.g. sand, earth, vermiculite, diatomaceous earth and place in container for disposal according to local regulations (see section 13). Clean preferably with a detergent - avoid use of solvents.

### 6.4 Reference to other sections

No data available.

## SECTION 7: Handling and storage

### 7.1 Precautions for safe handling

#### Advice on safe handling

Comply with the health and safety at work laws. Ensure adequate ventilation.

#### General protective and hygiene measures

Do not eat or drink during work - no smoking. Wash hands before breaks and after work. Avoid contact with eyes and skin. Observe the usual precautions when handling chemicals.

#### Advice on protection against fire and explosion

Keep away from sources of ignition - refrain from smoking. Take precautionary measures against static charges.

### 7.2 Conditions for safe storage, including any incompatibilities

#### Technical measures and storage conditions

Always keep in containers of same material as the original one. See also instructions on the label. Avoid heating and direct sunlight. Keep container dry in a cool, well-ventilated place.

#### Recommended storage temperature

Value	<	50	°C
-------	---	----	----

#### Requirements for storage rooms and vessels

Storage rooms must be properly ventilated.

#### Incompatible products

Keep away from oxidizing agents, from strongly alkaline and strongly acid materials. Do not store together with foodstuffs.

### 7.3 Specific end use(s)

No data available.

## SECTION 8: Exposure controls/personal protection

### 8.1 Control parameters

# EU safety data sheet

**Trade name:** Multi Multifunktionsölspray

**Product no.:** L27

**Current version :** 5.0.0, issued: 05.05.2021

**Replaced version:** 4.1.0, issued: 24.02.2021

**Region:** GB

## Occupational exposure limit values

No	Substance name	CAS no.	EC no.
1	butane	106-97-8	203-448-7
List of approved workplace exposure limits (WELs) / EH40			
	Butane		
	WEL short-term (15 min reference period)	1810 mg/m <sup>3</sup>	750 ppm
	WEL long-term (8-hr TWA reference period)	1450 mg/m <sup>3</sup>	600 ppm
	Comments	Carc, (only applies if Butane contains more than 0.1% of buta-1,3-diene)	

## DNEL, DMEL and PNEC values

### DNEL values (worker)

DNEL values (worker)					
No	Substance name			CAS / EC no	
	Route of exposure	Exposure time	Effect	Value	
1	Naphtha (petroleum), hydrotreated light			64742-49-0 920-750-0	
	dermal	Long term (chronic)	systemic	773	mg/kg/day
	inhalative	Long term (chronic)	systemic	2035	mg/m³

### DNEL value (consumer)

DNEL value (consumer)				CAS / EC no	
No	Substance name			Value	
	Route of exposure	Exposure time	Effect		
1	Naphtha (petroleum), hydrotreated light			64742-49-0 920-750-0	
	oral	Long term (chronic)	systemic	699	mg/kg
	dermal	Long term (chronic)	systemic	699	mg/kg/day
	inhalative	Long term (chronic)	systemic	608	mg/m³

## 8.2 Exposure controls

### Appropriate engineering controls

Provide adequate ventilation. Where reasonably practicable this should be achieved by the use of local exhaust ventilation and good general extraction. If these are not sufficient to maintain concentrations of particulates and solvent vapour below the OEL, suitable respiratory protection must be worn.

### Personal protective equipment

#### Respiratory protection

If workers are exposed to concentrations above the exposure limit they must use appropriate, certified respirators: Use half-mask model with cartridge or air-fed. Recommendation: gas filter AX, code colour: brown

#### Eye / face protection

Tightly fitting safety glasses (EN 166).

#### Hand protection

Sufficient protection is given wearing suitable protective gloves checked according to i.e. EN 374, in the event of risk of skin contact with the product. Before use, the protective gloves should be tested in any case for its specific work-station suitability (i.e. mechanical resistance, product compatibility and antistatic properties). Adhere to the manufacturer's instructions and information relating to the use, storage, care and replacement of protective gloves. Protective gloves shall be replaced immediately when physically damaged or worn. Design operations thus to avoid permanent use of protective gloves.

In case of short-term contact / splash protection:

Appropriate Material butyl rubber  
Material thickness > 0.7 mm

#### Other

Personal should wear antistatic clothings made of natural fiber or of high temperature resistant synthetic fiber. All parts of the body should be washed after contact.

### Environmental exposure controls

No data available.

# EU safety data sheet

**Trade name:** Multi Multifunktionsölspray

**Product no.:** L27

**Current version :** 5.0.0, issued: 05.05.2021

**Replaced version:** 4.1.0, issued: 24.02.2021

**Region:** GB

## SECTION 9: Physical and chemical properties

### 9.1 Information on basic physical and chemical properties

State of aggregation			
liquid			
Form/Colour			
Aerosol			
brownish			
Odour			
characteristic			
pH value			
No data available			
Boiling point / boiling range			
Not applicable			
Melting point/freezing point			
No data available			
Decomposition temperature			
No data available			
Flash point			
Not applicable			
Ignition temperature			
No data available			
Auto-ignition temperature			
Value	>	250	°C
Flammability			
No data available			
Lower explosion limit			
Value		3	% vol
Upper explosion limit			
Value		15	% vol
Vapour pressure			
Value		3.8	bar
Reference temperature		20	°C
Value		6.8	bar
Reference temperature		50	°C
Relative vapour density			
No data available			
Relative density			
No data available			
Density			
Value		0.65	g/cm³
Reference temperature		20	°C
Solubility in water			
Comments	insoluble		
Solubility			

# EU safety data sheet

**Trade name:** Multi Multifunktionsölspray

**Product no.:** L27

**Current version :** 5.0.0, issued: 05.05.2021

**Replaced version:** 4.1.0, issued: 24.02.2021

**Region:** GB

No data available
-------------------

Partition coefficient n-octanol/water (log value)			
No	Substance name	CAS no.	EC no.
1	propane	74-98-6	200-827-9
log Pow		appr.	1.8
Method		QSAR	
Source		ECHA	
2	isobutane	75-28-5	200-857-2
log Pow		2.80	
Reference temperature		20	°C
with reference to		pH 7	
Source		ECHA	

Viscosity
No data available

Particle characteristics
No data available

## 9.2 Other information

Other information
No data available.

## SECTION 10: Stability and reactivity

### 10.1 Reactivity

No data available.

### 10.2 Chemical stability

Stable if stored and handled properly.

### 10.3 Possibility of hazardous reactions

No data available.

### 10.4 Conditions to avoid

Stable under recommended storage and handling conditions(See section 7).

### 10.5 Incompatible materials

Keep away from oxidizing agents, strongly alkaline and strongly acid materials in order to avoid exothermic reactions.

### 10.6 Hazardous decomposition products

When exposed to high temperatures may produce hazardous decomposition products such as carbon monoxide and dioxide, smoke, oxides of nitrogen.

## SECTION 11: Toxicological information

### 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute oral toxicity			
No	Substance name	CAS no.	EC no.
1	Naphtha (petroleum), hydrotreated light	64742-49-0	920-750-0
LD50	>	5840	mg/kg bodyweight
Species	rat		
Source	ECHA		
Acute dermal toxicity			
No	Substance name	CAS no.	EC no.
1	Naphtha (petroleum), hydrotreated light	64742-49-0	920-750-0
LD50	> 2800	- 3100	mg/kg bodyweight
Species	rabbit		

# EU safety data sheet

**Trade name:** Multi Multifunktionsölspray

**Product no.:** L27

**Current version :** 5.0.0, issued: 05.05.2021

**Replaced version:** 4.1.0, issued: 24.02.2021

**Region:** GB

Source		ECHA	
Acute inhalational toxicity			
No	Substance name	CAS no.	EC no.
1	Naphtha (petroleum), hydrotreated light	64742-49-0	920-750-0
LC50	>	23.3	mg/l
Duration of exposure		4	h
State of aggregation	Vapour		
Species	rat		
Method	OECD 403		
Source	ECHA		
2 propane74-98-6200-827-9			
LC50	>	800000	ppmV
Duration of exposure		0.25	h
State of aggregation	Gas		
Species	rat		
Source	ECHA		
Evaluation/classification	Based on available data, the classification criteria are not met.		
3 isobutane75-28-5200-857-2			
LC50		520400	ppmV
Duration of exposure		2	h
State of aggregation	Gas		
Species	mouse		
Source	ECHA		
Evaluation/classification	Based on available data, the classification criteria are not met.		
Skin corrosion/irritation			
No	Substance name	CAS no.	EC no.
1	Naphtha (petroleum), hydrotreated light	64742-49-0	920-750-0
Species	rabbit		
Method	OECD 404		
Source	ECHA		
Evaluation	non-irritant		
Serious eye damage/irritation			
No	Substance name	CAS no.	EC no.
1	Naphtha (petroleum), hydrotreated light	64742-49-0	920-750-0
Species	rabbit		
Source	ECHA		
Evaluation	non-irritant		
Respiratory or skin sensitisation			
No	Substance name	CAS no.	EC no.
1	Naphtha (petroleum), hydrotreated light	64742-49-0	920-750-0
Route of exposure	Skin		
Species	guinea pig		
Method	OECD 406		
Source	ECHA		
Evaluation	non-sensitizing		
Germ cell mutagenicity			
No	Substance name	CAS no.	EC no.
1	Naphtha (petroleum), hydrotreated light	64742-49-0	920-750-0
Source	ECHA		
Evaluation/classification	Based on available data, the classification criteria are not met.		
2 isobutane75-28-5200-857-2			
Type of examination	in vitro gene mutation study in bacteria		
Species	Salmonella typh. TA98, TA100, TA1535, TA1537, TA1538		
Method	Value taken from the literature		



# EU safety data sheet

**Trade name:** Multi Multifunktionsölspray

**Product no.:** L27

**Current version :** 5.0.0, issued: 05.05.2021

**Replaced version:** 4.1.0, issued: 24.02.2021

**Region:** GB

Source	ECHA
Evaluation/classification	Based on available data, the classification criteria are not met.

Reproduction toxicity			
No	Substance name	CAS no.	EC no.
1	Naphtha (petroleum), hydrotreated light	64742-49-0	920-750-0
Source		ECHA	
Evaluation/classification		Based on available data, the classification criteria are not met.	
2	propane	74-98-6	200-827-9
Route of exposure		inhalational	
NOAEC		12000	ppm
Type of examination		Combined Repeated Dose Toxicity Study with the Reproduction/Developmental Toxicity Screening Test	
Species		rat	
Method		OECD 422	
Source		ECHA	
Evaluation/classification		Based on available data, the classification criteria are not met.	
3	isobutane	75-28-5	200-857-2
Route of exposure		inhalational	
NOAEC		9000	ppm
Type of examination		Combined Repeated Dose Toxicity Study with the Reproduction/Developmental Toxicity Screening Test	
Species		rat	
Method		OECD 422	
Source		ECHA	
Evaluation/classification		Based on available data, the classification criteria are not met.	

Carcinogenicity	
No data available	

STOT - single exposure	
No data available	

STOT - repeated exposure			
No	Substance name	CAS no.	EC no.
1	propane	74-98-6	200-827-9
Route of exposure		inhalational	
LOAEC		12000	ppm
Species		rat	
Method		OECD 422	
Source		ECHA	
Evaluation/classification		Based on available data, the classification criteria are not met.	
2	isobutane	75-28-5	200-857-2
Route of exposure		inhalational	
		9000	ppm
Species		rat	
Method		OECD 422	
Source		ECHA	
Evaluation/classification		Based on available data, the classification criteria are not met.	

Aspiration hazard	
No data available	

Delayed and immediate effects as well as chronic effects from short and long-term exposure	
Repeated or prolonged contact with the mixture may cause removal of natural fat from the skin resulting in non-allergic contact dermatitis and absorption through the skin. The liquid splashed in the eyes may cause irritation and reversible damage.	

## 11.2 Information on other hazards

Endocrine disrupting properties

# EU safety data sheet

**Trade name:** Multi Multifunktionsölspray

**Product no.:** L27

**Current version :** 5.0.0, issued: 05.05.2021

**Replaced version:** 4.1.0, issued: 24.02.2021

**Region:** GB

No data available.

**Other information**

No data available.

## SECTION 12: Ecological information

### 12.1 Toxicity

Toxicity to fish (acute)			
No	Substance name	CAS no.	EC no.
1	Naphtha (petroleum), hydrotreated light	64742-49-0	920-750-0
LL50		<=	10 mg/l
Duration of exposure			96 h
Species	Oncorhynchus mykiss		
Method	OECD 203		
Source	ECHA		

Toxicity to fish (chronic)			
No	Substance name	CAS no.	EC no.
1	Naphtha (petroleum), hydrotreated light	64742-49-0	920-750-0
NOELR		0.57	mg/l
Duration of exposure		28	day(s)
Species	Oncorhynchus mykiss		
Source	ECHA		

Toxicity to Daphnia (acute)			
No	Substance name	CAS no.	EC no.
1	Naphtha (petroleum), hydrotreated light	64742-49-0	920-750-0
EL50		<=	10 mg/l
Duration of exposure		48	h
Species	Daphnia magna		
Method	OECD 202		
Source	ECHA		

Toxicity to Daphnia (chronic)			
No	Substance name	CAS no.	EC no.
1	Naphtha (petroleum), hydrotreated light	64742-49-0	920-750-0
NOELR		1	mg/l
Duration of exposure		21	day(s)
Species	Daphnia magna		
Method	OECD 211		
Source	ECHA		

Toxicity to algae (acute)			
No	Substance name	CAS no.	EC no.
1	Naphtha (petroleum), hydrotreated light	64742-49-0	920-750-0
EL50		<=	30 mg/l
Duration of exposure		72	h
Species	Pseudokirchneriella subcapitata		
Method	OECD 201		
Source	ECHA		

Toxicity to algae (chronic)			
No	Substance name	CAS no.	EC no.
1	Naphtha (petroleum), hydrotreated light	64742-49-0	920-750-0
NOELR		6.3	mg/l
Duration of exposure		3	day(s)
Species	Pseudokirchneriella subcapitata		
Method	OECD 201		
Source	ECHA		

# EU safety data sheet

**Trade name:** Multi Multifunktionsölspray

**Product no.:** L27

**Current version :** 5.0.0, issued: 05.05.2021

**Replaced version:** 4.1.0, issued: 24.02.2021

**Region:** GB

## Bacteria toxicity

No data available

## 12.2 Persistence and degradability

Biodegradability			
No	Substance name	CAS no.	EC no.
1	Naphtha (petroleum), hydrotreated light	64742-49-0	920-750-0
	Value	98	%
	Duration	28	day(s)
	Method	OECD 301 F	
	Source	ECHA	
	Evaluation	readily biodegradable	
2	propane	74-98-6	200-827-9
	Type	aerobic biodegradation	
	Value	50	%
	Duration	3	d
	Method	QSAR	
	Source	ECHA	
	Evaluation	readily biodegradable	
3	isobutane	75-28-5	200-857-2
	Type	aerobic biodegradation	
	Value	50	%
	Duration	3.1	d
	Method	QSAR	
	Source	ECHA	
	Evaluation	readily biodegradable	

## 12.3 Bioaccumulative potential

Partition coefficient n-octanol/water (log value)			
No	Substance name	CAS no.	EC no.
1	propane	74-98-6	200-827-9
	log Pow	appr.	1.8
	Method	QSAR	
	Source	ECHA	
2	isobutane	75-28-5	200-857-2
	log Pow	2.80	
	Reference temperature	20	°C
	with reference to	pH 7	
	Source	ECHA	

## 12.4 Mobility in soil

No data available.

## 12.5 Results of PBT and vPvB assessment

No data available.

## 12.6 Endocrine disrupting properties

No data available.

## 12.7 Other adverse effects

No data available.

## 12.8 Other information

Other information
The product should not be allowed to enter drains or water courses.

## SECTION 13: Disposal considerations

### 13.1 Waste treatment methods

# EU safety data sheet

**Trade name:** Multi Multifunktionsölspray

**Product no.:** L27

**Current version :** 5.0.0, issued: 05.05.2021

**Replaced version:** 4.1.0, issued: 24.02.2021

**Region:** GB

## Product

Allocation of a waste code number, according to the European Waste Catalogue, should be carried out in agreement with the regional waste disposal company.

Hand over only completely emptied aerosol cans for valuable substance recovery!

## Packaging

Contaminated packaging should be emptied as far as possible and after appropriate cleansing may be taken for reuse. Packaging that cannot be cleaned should be disposed of in agreement with the regional waste disposal company.

## SECTION 14: Transport information

### 14.1 Transport ADR/RID/ADN

Class	2
Classification code	5F
UN number	UN1950
Proper shipping name	AEROSOLS
Tunnel restriction code	D
Label	2.1

### 14.2 Transport IMDG

Class	2
UN number	UN1950
Proper shipping name	AEROSOLS
EmS	F-D, S-U
Label	2.1

### 14.3 Transport ICAO-TI / IATA

Class	2.1
UN number	UN1950
Proper shipping name	Aerosols, flammable
Label	2.1

### 14.4 Other information

No data available.

### 14.5 Environmental hazards

Information on environmental hazards, if relevant, please see 14.1 - 14.3.

### 14.6 Special precautions for user

No data available.

### 14.7 Maritime transport in bulk according to IMO instruments

Not relevant

## SECTION 15: Regulatory information

### 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

#### EU regulations

#### **Regulation (EC) No 1907/2006 (REACH) Annex XIV (List of substances subject to authorisation)**

According to the data available and/or specifications supplied by upstream suppliers, this product does not contain any substances considered as substances requiring authorisation as listed on Annex XIV of the REACH regulation (EC) 1907/2006.

#### **REACH candidate list of substances of very high concern (SVHC) for authorisation**

According to available data and the information provided by preliminary suppliers, the product does not contain substances that are considered substances meeting the criteria for inclusion in annex XIV (List of Substances Subject to Authorisation) as laid down in Article 57 and article 59 of REACH (EC) 1907/2006.

#### **Regulation (EC) No 1907/2006 (REACH) Annex XVII: RESTRICTIONS ON THE MANUFACTURE, PLACING ON**

# EU safety data sheet

**Trade name:** Multi Multifunktionsölspray

**Product no.:** L27

**Current version :** 5.0.0, issued: 05.05.2021

**Replaced version:** 4.1.0, issued: 24.02.2021

**Region:** GB

THE MARKET AND USE OF CERTAIN DANGEROUS SUBSTANCES, MIXTURES AND ARTICLES	
The product is considered being subject to REACH regulation (EC) 1907/2006 annex XVII.	No 3
Directive 2012/18/EU on the control of major-accident hazards involving dangerous substances	
This product is subject to Part I of Annex I, risk category:	P3a
Directive 2010/75/EU on industrial emissions (integrated pollution prevention and control)	
VOC content	77.4 %
VOC-value	503.1 g/l
Other regulations	
Adhere to the national sanitary and occupational safety regulations when using this product.	

## 15.2 Chemical safety assessment

No data available.

## SECTION 16: Other information

### Sources of key data used to compile the data sheet:

Regulation (EC) No 1907/2006 (REACH), 1272/2008 (CLP) as amended in each case.

Directives 2000/39/EC, 2006/15/EC, 2009/161/EU, (EU) 2017/164.

National Threshold Limit Values of the corresponding countries as amended in each case.

Transport regulations according to ADR, RID, IMDG, IATA as amended in each case.

The data sources used to determine physical, toxic and ecotoxic data, are indicated directly in the corresponding section.

### Full text of the H- and EUH- phrases drawn up in sections 2 and 3 (provided not already drawn up in these sections)

H220	Extremely flammable gas.
H225	Highly flammable liquid and vapour.
H280	Contains gas under pressure; may explode if heated.
H304	May be fatal if swallowed and enters airways.
H411	Toxic to aquatic life with long lasting effects.

### Notes relating to the identification, classification and labelling of substances and mixtures ((EC) No 1272/2008, Annex VI)

C	Some organic substances may be marketed either in a specific isomeric form or as a mixture of several isomers. In this case the supplier must state on the label whether the substance is a specific isomer or a mixture of isomers.
U	When put on the market gases have to be classified as 'Gases under pressure', in one of the groups compressed gas, liquefied gas, refrigerated liquefied gas or dissolved gas. The group depends on the physical state in which the gas is packaged and therefore has to be assigned case by case.

This information is based on our present knowledge and experience.

The safety data sheet describes products with a view to safety requirements.

It does not however, constitute a guarantee for any specific product properties and shall not establish a legally valid contractual relationship.

### Alterations/supplements:

Alterations to the previous edition are marked in the left-hand margin.

Document protected by copyright. Alterations or reproductions require the express written permission of UMCÖ GmbH.

Prod-ID 616917