

1-core outdoor slip-on cable termination

for 1-core polymeric cables

Contrax cable terminations CAE-F are suitable for all 1-core polymeric-insulated cables (PVC, PE, XLPE, EPR) with different types of semi-conductive layers (graphitecoated, removable or strippable) and screen design (wire or tape). Suitable for compression cable lugs.



Product description

Article name	CAE-F 36kV 120-400
Article number	199199
Notes	Can be used also for cables Um = 7,2 kV, then the minimum diameter over conductor insulation has to be checked.
Optional accessory	EGA earthing kit for cables with tape screen (see Connecting technology) Compression cable lugs (see Connecting technology)

Characteristics

Silicone slip-on components for quick, safe and easy assembly


Wide cross-section range

Ready for immediate operation

Applications

Outdoor

Technical data



Article name	CAE-F 36kV 120-400
Article number	199199
Voltage levels	U0/U (Um) 18/30 (36) kV - 19/33 (36) kV
Test standards	CENELEC HD 629.1
Length L	440 mm
Diameter over core insulation after removal of the outer conductive layer min	27.3 mm
Number of sheds per phase	5 Pieces
Diameter shed	97 mm
Nominal cross section 36 kV min	120 mm²
Nominal cross section 36 kV max	400 mm²

Logistics data

Article name	CAE-F 36kV 120-400
Article number	199199
Delivery scope	3 One-piece slip-on silicone cable terminations with integrated stress control element
	Silicone tubes
	Sealing tape
	Assembly material
	Assembly instructions
Shelf life description	Unlimited shelf life
Country of origin	Germany
Customs tariff number	85469090
EAN/GTIN	4010311054872

Packaging data

Alternative unit of measure	Carton	Pal. OW
Base quantity	1	30
Base unit of measure	Piece	Piece
Length (mm)	430	1200
Width (mm)	268	800
Height (mm)	157	1130
Net weight (kg)	1.598	47.94
Gross weight (kg)	1.598	75.728