

Eindsluiting koude opschuif voor 1-aderige kabel binnen

voor 1-aderige kunststof kabels

Contrax eindsluitingen CAE-I zijn geschikt voor alle 1-aderige kunststof geïsoleerde kabels (PVC, PE, VPE, EPR) met verschillende geleidende lagen (met grafietlaag, aftrek- of afschilbaar) en schermvormgevingen (scherm van koperdraad of band). Geschikt voor perskabelschoenen.



Produktbeschrijving

Artikelbeschrijving	CAE-I 24kV 35-120
Artikelnummer	199162
Notities	Ook voor $U_m = 7,2$ kV te gebruikt. (De min. diameter boven de aderisolatie worden gecontroleerd.)
Optioneel toebehoren	EGA aardingskit voor kunstof kabel (zie Verbindingstechniek) Pers kabelschoenen (zie Verbindingstechniek)

Eigenschappen

Snelle, eenvoudige en veilige montage door siliconen-opschuifcomponenten

Groot diameterbereik

Direct operationeel

Toepassing

Binnen

Technical drawing of a cable clamp. The drawing shows a side view of the clamp with a central screw. Dimensions are indicated: a diameter of 5 mm (Ø 5) for the top part and a length of 130 mm for the main body. The drawing is labeled with 'Ø 5' and '130'.

part	description	quantity	unit
1	Clamp	270	mm
Ø 5	clamp diameter	5	mm

part	description	quantity	unit
1	Clamp	270	mm
Ø 5	clamp diameter	5	mm

part	description	quantity	unit
1	Clamp	270	mm
Ø 5	clamp diameter	5	mm

part	description	quantity	unit
1	Clamp	270	mm
Ø 5	clamp diameter	5	mm

part	description	quantity	unit
1	Clamp	270	mm
Ø 5	clamp diameter	5	mm

part	description	quantity	unit
1	Clamp	270	mm
Ø 5	clamp diameter	5	mm

part	description	quantity	unit
1	Clamp	270	mm
Ø 5	clamp diameter	5	mm

part	description	quantity	unit
1	Clamp	270	mm
Ø 5	clamp diameter	5	mm

part	description	quantity	unit
1	Clamp	270	mm
Ø 5	clamp diameter	5	mm

part	description	quantity	unit
1	Clamp	270	mm
Ø 5	clamp diameter	5	mm

part	description	quantity	unit
1	Clamp	270	mm
Ø 5	clamp diameter	5	mm

part	description	quantity	unit
1	Clamp	270	mm
Ø 5	clamp diameter	5	mm

part	description	quantity	unit
1	Clamp	270	mm
Ø 5	clamp diameter	5	mm

part	description	quantity	unit
1	Clamp	270	mm
Ø 5	clamp diameter	5	mm

part	description	quantity	unit
1	Clamp	270	mm
Ø 5	clamp diameter	5	mm

part	description	quantity	unit
1	Clamp	270	mm
Ø 5	clamp diameter	5	mm

part	description	quantity	unit
1	Clamp	270	mm
Ø 5	clamp diameter	5	mm

part	description	quantity	unit
1	Clamp	270	mm
Ø 5	clamp diameter	5	mm

part	description	quantity	unit
1	Clamp	270	mm
Ø 5	clamp diameter	5	mm

part	description	quantity	unit
1	Clamp	270	mm
Ø 5	clamp diameter	5	mm

part	description	quantity	unit
1	Clamp	270	mm
Ø 5	clamp diameter	5	mm

part	description	quantity	unit
1	Clamp	270	mm
Ø 5	clamp diameter	5	mm

part	description	quantity	unit
1	Clamp	270	mm
Ø 5	clamp diameter	5	mm

part	description	quantity	unit
1	Clamp	270	mm
Ø 5	clamp diameter	5	mm

part	description	quantity	unit
1	Clamp	270	mm
Ø 5	clamp diameter	5	mm

part	description	quantity	unit
1	Clamp	270	mm
Ø 5	clamp diameter	5	mm

part	description	quantity	unit
1	Clamp	270	mm
Ø 5	clamp diameter	5	mm

part	description	quantity	unit
1	Clamp	270	mm
Ø 5	clamp diameter	5	mm

part	description	quantity	unit
1	Clamp	270	mm
Ø 5	clamp diameter	5	mm

part	description	quantity	unit
1			

Artikelbeschrijving	CAE-I 24kV 35-120
Artikelnummer	199162
Spanningsniveaus	U0/U (Um) 12/20 (24) kV - 12,7/22 (24) kV
Testrapporten	CENELEC HD 629.1
Lengte L	270 mm
Diameter over core insulation after removal of the outer conductive layer min	17.3 mm
Number of sheds per phase	1 Stuks
Diameter shed	87 mm
Nominal cross section 24 kV min	35 mm ²
Nominal cross section 24 kV max	120 mm ²

Logistieke gegevens

Artikelbeschrijving	CAE-I 24kV 35-120
Artikelnummer	199162
Levering	3 x 1-Delige opschuifbare siliconen-eindsluitingen met geïntegreerde veldsturing
	Siliconen-slang
	Afdichtingsband
	Klein montagemateriaal
	Montagehandleiding
Duurzaamheid aanvullende teksten	Onbeperkt houdbaar
Land van oorsprong	Duitsland
Douanetariefnummer	85469090
EAN/GTIN	4010311054506

Verpakkingsgegevens

Alternatieve maateenheid	Karton	Pallet EW
Basishoeveelheid	1	84
Basis maateenheid	Stuk	Stuk
Lengte (mm)	383	1200
Breedte (mm)	189	800
Hoogte (mm)	132	1130
Netto gewicht (kg)	0.798	67.032
Bruto gewicht (kg)	0.798	85.232