

## 3-core straight-through joint with screw cable lugs

with heat shrinkable outer protection for 3-core polymeric cables

Contrax straight-through joints CAMSV-3S are suitable for all 3-core polymeric insulated cables (PVC, PE, XLPE, EPR). They allow the connection of cables with different cross sections and conductor materials even with different cable designs concerning the semi-conductive layer (removable or strippable) and screen design (copper wire or tape screen). With screw connectors.



### Product description

Article name	CAMSV-3S 24kV 95-300
Article number	355017

## Technical data

Article name	CAMSV-3S 24kV 95-300
Article number	355017
Voltage levels	U0/U (Um) 6/10 (12) kV - 12,7/22 (24) kV
Length L	1230 m
Diameter over core insulation after removal of the outer conductive layer min	22 mm
Nominal cross section 12 kV min	150 mm <sup>2</sup>
Nominal cross section 12 kV max	300 mm <sup>2</sup>
Nominal cross section 17,5 kV min	120 mm <sup>2</sup>
Nominal cross section 17,5 kV max	300 mm <sup>2</sup>
Nominal cross section 24 kV min	95 mm <sup>2</sup>
Nominal cross section 24 kV max	300 mm <sup>2</sup>

## Logistics data

Article name	CAMSV-3S 24kV 95-300
Article number	355017
Country of origin	Germany
Customs tariff number	39269097
EAN/GTIN	4010311171548

## Packaging data

Packaging type	Carton	Pal. OW
Content quantity	1	12
Unit of measure	Piece	Piece
Length (mm)	874	1200
Width (mm)	385	800
Height (mm)	180	1130
Net weight (kg)	5.285	63.42
Gross weight (kg)	5.285	81.62