

3-core straight-through joint with screw cable lugs

with heat shrinkable outer protection for 3-core polymeric cables

Contrax straight-through joints CAMSV-3S are suitable for all 3-core polymeric insulated cables (PVC, PE, XLPE, EPR). They allow the connection of cables with different cross sections and conductor materials even with different cable designs concerning the semi-conductive layer (removable or strippable) and screen design (copper wire or tape screen). With screw connectors.



Product description

| | |
|----------------|---------------------|
| Article name | CAMSV-3S 24kV 35-95 |
| Article number | 370731 |

Technical data

| | |
|---|--|
| Article name | CAMSV-3S 24kV 35-95 |
| Article number | 370731 |
| Voltage levels | U0/U (Um) 6/10 (12) kV - 12,7/22 (24) kV |
| Length L | 1230 m |
| Diameter over core insulation after removal of the outer conductive layer min | 16.5 mm |
| Nominal cross section 12 kV min | 70 mm ² |
| Nominal cross section 12 kV max | 150 mm ² |
| Nominal cross section 17,5 kV min | 50 mm ² |
| Nominal cross section 17,5 kV max | 120 mm ² |
| Nominal cross section 24 kV min | 35 mm ² |
| Nominal cross section 24 kV max | 95 mm ² |

Logistics data

| | |
|-----------------------|---------------------|
| Article name | CAMSV-3S 24kV 35-95 |
| Article number | 370731 |
| Country of origin | Germany |
| Customs tariff number | 39269097 |
| EAN/GTIN | 4010311181691 |

Packaging data

| | | |
|-------------------|--------|---------|
| Packaging type | Carton | Pal. OW |
| Content quantity | 1 | 12 |
| Unit of measure | Piece | Piece |
| Length (mm) | 865 | 1200 |
| Width (mm) | 369 | 800 |
| Height (mm) | 170 | 1130 |
| Net weight (kg) | 3.598 | 43.176 |
| Gross weight (kg) | 3.598 | 61.376 |