

1-core straight-through joint
with screw connector and cold shrinkable outer protection

Contrax-Straight-through joints CAMSV-C are suitable for all 1-core polymericinsulated cables (PVC, PE, XLPE, EPR). They allow the connection of cables with different cross sections and conductor materials even with different cable designs concerning the semi-conductive layer (removable or strippable) and screen design (wire or tape screen). With screw connector.



Product description

Article name	CAMSV-C 24kV 35-95
Article number	370725
Notes	Can be used also for cables Um = 7,2 kV, then the minimum diameter over conductor insulation has to be checked.

Characteristics

Slip-on silicone joint unit with integrated stress control element
Wide conductor and cross-section range
Suitable for a wide range of applications due to integrated screw connector
For both copper and aluminium conductors
Few components, compact design and reduced working length
With cold shrinkable outer protection
Quick, safe and easy assembly
Ready for immediate operation

Applications

Indoor
Outdoor
Underground
Water
Installation ducts
Ductwork

Article name	CAMSV-C 24kV 35-95
Article number	370725
Voltage levels	U0/U (Um) 6/10 (12) kV - 12,7/22 (24) kV
Test standards	CENELEC HD 629.1
Length L	530 mm
Diameter over core insulation after removal of the outer conductive layer min	16.5 mm
Nominal cross section 12 kV min	70 mm ²
Nominal cross section 12 kV max	150 mm ²
Nominal cross section 17,5 kV min	50 mm ²
Nominal cross section 17,5 kV max	120 mm ²
Nominal cross section 24 kV min	35 mm ²
Nominal cross section 24 kV max	95 mm ²

Logistics data

Article name	CAMSV-C 24kV 35-95
Article number	370725
Delivery scope	Cold shrinkable outer tube
	Silicone joint body with integrated inner and outer semiconductive layer (individually tested)
	Screw connector
	Copper braid tube
	Pressure springs
	Sealing tape
	Assembly instructions
Shelf life	36 Month
Storage temperatur max	40 °C
Storage temperatur min	0 °C
Country of origin	Germany
Customs tariff number	39269097
EAN/GTIN	4010311181653

Packaging data

Alternative unit of measure	Carton	Pal. OW
Base quantity	1	42
Base unit of measure	Piece	Piece
Lenght (mm)	725	1200
Width (mm)	167	800
Height (mm)	160	1100
Net weight (kg)	1.252	52.584
Gross weight (kg)	1.252	70.784