

3-core indoor cable termination
for 3-core trailing cables

Combination of slip-on and heat shrinkable components for 3-core trailing cables. Suitable for compression or screw cable lugs.



Product description

Article name	CHE-3I(T) 7,2kV 70-120
Article number	169459
Notes	Other cable terminations available on request.
Optional accessory	Cable lugs (see Connecting technology)

Characteristics
Flexible silicone stress control elements ensure reliable stress control under all operating conditions
Wide cross-section range
Quick, safe and easy assembly
Ready for immediate operation

Applications
Indoor

Technical data

Article name	CHE-3I(T) 7,2kV 70-120
Article number	169459
Voltage levels	U0/U (Um) 3,6/6 (7,2) kV - 3,8/6,6 (7,2) kV
Nominal cross section 36 kV min	70 mm ²
Nominal cross section 36 kV max	120 mm ²

Logistics data

Article name	CHE-3I(T) 7,2kV 70-120
Article number	169459
Delivery scope	Spreader cap
	Heat shrinkable tube (tracking resistant)
	Heat shrinkable tube medium-walled
	Silicone field control elements
	Silicone sheds
	Sealing tape
	Assembly material
	Assembly instructions
Shelf life description	Unlimited shelf life
Country of origin	Germany
Customs tariff number	85469090
EAN/GTIN	4010311040998

Packaging data

Alternative unit of measure	Carton	Pal. OW
Base quantity	1	84
Base unit of measure	Piece	Piece
Length (mm)	435	1200
Width (mm)	175	800
Height (mm)	175	1130
Net weight (kg)	1.377	115.668
Gross weight (kg)	1.377	133.868