

1-core outdoor cable termination
for 1-core polymeric cables

Hybrid cable terminations CHE-F are suitable for all 1-core polymeric-insulated cables (PVC, PE, XLPE, EPR) with different types of semi-conductive layers (graphitecoated, removable or strippable) and screen design (copper wire or tape). Suitable for compression or screw cable lugs.




Product description

Article name	CHE-F 17kV 10-16
Article number	194056
Notes	Can be used also for cables Um = 7,2 kV, then the minimum diameter over conductor insulation has to be checked.
Optional accessory	EGA earthing kit for cables with tape screen (see Connecting technology) Compression cable lugs (see Connecting technology)

Characteristics
Flexible silicone stress control elements ensure reliable stress control under all operating conditions
Combination of slip-on and heat shrinkable components
Wide cross-section range
Quick, safe and easy assembly
Ready for immediate operation

Applications
Outdoor

Technical data



Article name	CHE-F 17kV 10-16
Article number	194056
Voltage levels	U0/U (Um) 8,7/15 (17,5) kV
Test standards	CENELEC HD 629.1
Length L	500 mm
Diameter over core insulation after removal of the outer conductive layer min	9.9 mm
Diameter over core insulation after removal of the outer conductive layer max	9.9 mm
Number of sheds per phase	2 Pieces
Diameter shed	80 mm
Nominal cross section 17,5 kV min	10 mm ²
Nominal cross section 17,5 kV max	16 mm ²

Logistics data

Article name	CHE-F 17kV 10-16
Article number	194056
Delivery scope	Heat shrinkable tube (tracking resistant)
	Silicone field control elements
	Silicone sheds
	1 Set for 3 phases
	Sealing tape
	Assembly material
	Assembly instructions
Shelf life description	Unlimited shelf life
Country of origin	Germany
Customs tariff number	85469090
EAN/GTIN	4010311046969

Packaging data

Alternative unit of measure	Carton	Pal. OW
Base quantity	1	84
Base unit of measure	Piece	Piece
Length (mm)	385	1200
Width (mm)	190	800
Height (mm)	134	1130
Net weight (kg)	0.978	82.152
Gross weight (kg)	0.978	100.352