

## 1-core outdoor cable termination

for 1-core polymeric cables

Hybrid cable terminations CHE-F are suitable for all 1-core polymeric-insulated cables (PVC, PE, XLPE, EPR) with different types of semi-conductive layers (graphitecoated, removable or strippable) and screen design (copper wire or tape). Suitable for compression or screw cable lugs.



### Product description

Article name	CHE-F 17kV 630-1000
Article number	194063
Notes	Can be used also for cables $U_m = 7,2$ kV, then the minimum diameter over conductor insulation has to be checked.
Optional accessory	EGA earthing kit for cables with tape screen (see Connecting technology) Compression cable lugs (see Connecting technology)

#### Characteristics

Flexible silicone stress control elements ensure reliable stress control under all operating conditions

Combination of slip-on and heat shrinkable components

Wide cross-section range


Quick, safe and easy assembly

Ready for immediate operation

#### Applications

Outdoor

## Technical data



Article name	CHE-F 17kV 630-1000
Article number	194063
Voltage levels	U0/U (Um) 8,7/15 (17,5) kV
Test standards	CENELEC HD 629.1
Length L	500 mm
Diameter over core insulation after removal of the outer conductive layer min	36.8 mm
Diameter over core insulation after removal of the outer conductive layer max	36.8 mm
Number of sheds per phase	2 Pieces
Diameter shed	123 mm
Nominal cross section 17,5 kV min	630 mm <sup>2</sup>
Nominal cross section 17,5 kV max	1000 mm <sup>2</sup>

## Logistics data

Article name	CHE-F 17kV 630-1000
Article number	194063
Delivery scope	Heat shrinkable tube (tracking resistant)
	Silicone field control elements
	Silicone sheds
	1 Set for 3 phases
	Sealing tape
	Assembly material
	Assembly instructions
Shelf life description	Unlimited shelf life
Country of origin	Germany
Customs tariff number	85469090
EAN/GTIN	4010311047027

## Packaging data

Packaging type	Carton	Pal. OW
Content quantity	1	48
Unit of measure	Piece	Piece
Length (mm)	726	1200
Width (mm)	156	800
Height (mm)	132	1130
Net weight (kg)	2.16	103.68
Gross weight (kg)	2.16	121.88