

1-core outdoor cable termination with screw cable lugs for 1-core polymeric cables

Hybrid cable terminations CHESK-F are suitable for all 1-core polymeric-insulated cables (PVC, PE, XLPE, EPR) with different types of semi-conductive layers (graphitecoated, removable or strippable) and screen design (copper wire or tape). With screw cable lugs for main conductor and copper wire screen.



Product description

Article name	CHESK-F 36kV 400-630
Article number	369520
Notes	Can be used also for cables $U_m = 7,2$ kV, then the minimum diameter over conductor insulation has to be checked.
Optional accessory	EGA earthing kit for cables with tape screen (see Connecting technology)

Characteristics

Flexible silicone stress control elements ensure reliable stress control under all operating conditions

Combination of slip-on and heat shrinkable components

Wide cross-section range


Quick, safe and easy assembly

Ready for immediate operation

Applications

Outdoor

Technical data



Article name	CHESK-F 36kV 400-630
Article number	369520
Voltage levels	U0/U (Um) 18/30 (36) kV - 19/33 (36) kV
Test standards	CENELEC HD 629.1
Length L	700 mm
Diameter over core insulation after removal of the outer conductive layer min	36.8 mm
Number of sheds per phase	4 Pieces
Diameter shed	115 mm
Nominal cross section 36 kV min	400 mm ²
Nominal cross section 36 kV max	630 mm ²

Logistics data

Article name	CHESK-F 36kV 400-630
Article number	369520
Delivery scope	Heat shrinkable tube (tracking resistant) Silicone field control elements Silicone sheds Screw cable lugs 1 Set for 3 phases Sealing tape Assembly material Installation instruction
Shelf life description	Unlimited shelf life
Country of origin	Germany
Customs tariff number	85469090
EAN/GTIN	4010311180137

Packaging data

Packaging type	Carton	Pal. OW
Content quantity	1	25
Unit of measure	Piece	Piece
Length (mm)	730	1200
Width (mm)	165	800
Height (mm)	157	1130
Net weight (kg)	4.645	116.125
Gross weight (kg)	4.645	213.29