

Transition joint with screw connectors
from H-Type cables to polymeric three 1-core cables

Hybrid transition joints CHMP(H)SV3-1 for transition to three 1-core polymericinsulated cables, are suitable for H-Type cables for 24 kV. With screw connectors.



Product description

Article name	CHMP(H)SV3-1 24kV 35-95
Article number	336538

Characteristics
Reliable stress control due to flexible silicone stress control elements
Wide cross-section range
Quick, safe and easy assembly
Ready for immediate operation

Applications
Indoor
Outdoor
Underground
Water
Installation ducts
Ductwork

The drawing shows a cable assembly with a length of 22.00 mm. The cable has a diameter of 1.24 mm and a cross-section of 35-35. The cable is labeled with the part number 336538 and the manufacturer CELLPACK.

part / description		dimensions	
part	description	length	diameter
1	Cable	22.00 mm	1.24 mm

part / description		dimensions	
part	description	length	diameter
1	Cable	22.00 mm	1.24 mm

part / description		dimensions	
part	description	length	diameter
1	Cable	22.00 mm	1.24 mm

part / description		dimensions	
part	description	length	diameter
1	Cable	22.00 mm	1.24 mm

part / description		dimensions	
part	description	length	diameter
1	Cable	22.00 mm	1.24 mm

part / description		dimensions	
part	description	length	diameter
1	Cable	22.00 mm	1.24 mm

part / description		dimensions	
part	description	length	diameter
1	Cable	22.00 mm	1.24 mm

part / description		dimensions	
part	description	length	diameter
1	Cable	22.00 mm	1.24 mm

part / description		dimensions	
part	description	length	diameter
1	Cable	22.00 mm	1.24 mm

part / description		dimensions	
part	description	length	diameter
1	Cable	22.00 mm	1.24 mm

part / description		dimensions	
part	description	length	diameter
1	Cable	22.00 mm	1.24 mm

part / description		dimensions	
part	description	length	diameter
1	Cable	22.00 mm	1.24 mm

part / description		dimensions	
part	description	length	diameter
1	Cable	22.00 mm	1.24 mm

part / description		dimensions	
part	description	length	diameter
1	Cable	22.00 mm	1.24 mm

part / description		dimensions	
part	description	length	diameter
1	Cable	22.00 mm	1.24 mm

part / description		dimensions	
part	description	length	diameter
1	Cable	22.00 mm	1.24 mm

part / description		dimensions	
part	description	length	diameter
1	Cable	22.00 mm	1.24 mm

part / description		dimensions	
part	description	length	diameter
1	Cable	22.00 mm	1.24 mm

part / description		dimensions	
part	description	length	diameter
1	Cable	22.00 mm	1.24 mm

part / description		dimensions	
part	description	length	diameter
1	Cable	22.00 mm	1.24 mm

part / description		dimensions	
part	description	length	diameter
1	Cable	22.00 mm	1.24 mm

part / description		dimensions	
part	description	length	diameter
1	Cable	22.00 mm	1.24 mm

part / description		dimensions	
part	description	length	diameter
1	Cable	22.00 mm	1.24 mm

part / description		dimensions	
part	description	length	diameter
1	Cable	22.00 mm	1.24 mm

part / description		dimensions	
part	description	length	diameter
1	Cable	22.00 mm	1.24 mm

part / description		dimensions	
part	description	length	diameter
1	Cable	22.00 mm	1.24 mm

part / description		dimensions	
part	description	length	diameter
1	Cable	22.00 mm	1.24 mm

part / description		dimensions	
part	description	length	diameter
1	Cable	22.00 mm	1.24 mm

part / description		dimensions	
part	description	length	diameter
1	Cable	22.00 mm	1.24 mm

part / description		dimensions	
part	description	length	diameter
1	Cable	22.00 mm	1.24 mm

part / description	
--------------------	--

Article name	CHMP(H)SV3-1 24kV 35-95
Article number	336538
Voltage levels	U0/U (Um) 12/20 (24) kV - 12,7/22 (24) kV
Test standards	DIN VDE 0278-629-2
Length L	1100 mm
Diameter over core insulation after removal of the outer conductive layer min	17.3 mm
Nominal cross section 24 kV min	35 mm²
Nominal cross section 24 kV max	95 mm²

Logistics data

Article name	CHMP(H)SV3-1 24kV 35-95
Article number	336538
Delivery scope	Spreader cap
	Thick wall heat shrinkable outer tube with hot melt adhesive
	Oil barrier tubing
	Silicone field control elements
	Earthing wire
	Heat shrinkable tubes
	Copper braid tape
	Assembly material
	Pressure spring
	Field control filling tape (blue)
	Sealing tape
	Fire protection wrapping
	Innovative screw connector with conductive cover
	Assembly instructions
Shelf life description	Unlimited shelf life
Country of origin	Germany
Customs tariff number	39269097
EAN/GTIN	4010311165196

Packaging data

Alternative unit of measure	Carton	Pal. OW
Base quantity	1	12
Base unit of measure	Piece	Piece
Lenght (mm)	871	1200
Width (mm)	383	800
Height (mm)	195	1130
Net weight (kg)	5.796	69.552
Gross weight (kg)	5.796	87.752