

Transition joint

from belted cables / H-Type cables to three 1-core polymeric cables

Hybrid transition joints CHMPR3-1 for transition to three 1-core polymeric-insulated cables, are suitable for belted cables and H-Type cables up to 17.5 kV. The scope of application can be reduced by an appropriate padding set for the massimpregnated paper cable. Suitable for compression connectors.




Product description

Article name	CHMPR3-1 17kV 70-240
Article number	197604
Notes	Other transition joints available on request.
Optional accessory	Compression connectors (see Connecting technology)

Characteristics
Reliable stress control due to flexible silicone stress control elements
Wide cross-section range
Quick, safe and easy assembly
Ready for immediate operation

Applications
Indoor
Outdoor
Underground
Water
Installation ducts
Ductwork

Technical data



Article name	CHMPR3-1 17kV 70-240
Article number	197604
Voltage levels	U0/U (Um) 6/10 (12) kV - 8,7/15 (17,5) kV
Test standards	DIN VDE 0278-629-2
Diameter Connector 12kV max	34 mm
Diameter Connector 17,5kV max	34 mm
Length Connector 12kV max	145 mm
Length Connector 17,5kV max	145 mm
Length L	1100 mm
Diameter over core insulation after removal of the outer conductive layer min	17.3 mm
Nominal cross section 12 kV min	95 mm ²
Nominal cross section 12 kV max	240 mm ²
Nominal cross section 17,5 kV min	70 mm ²
Nominal cross section 17,5 kV max	240 mm ²

Logistics data

Article name	CHMPR3-1 17kV 70-240
Article number	197604
Delivery scope	Spreader cap Thick wall heat shrinkable outer tube with hot melt adhesive Oil barrier tubing Silicone field control elemens Earthing wire Heat shrinkable tubes Copper braid tape Assembly material Pressure spring Field control filling tape (blue) Sealing tape Fire protection wrapping Installation instruction
Shelf life description	Unlimited shelf life
Country of origin	Germany
Customs tariff number	39269097
EAN/GTIN	4010311051468

Packaging data

Packaging type	Carton	Pal. OW
Content quantity	1	12
Unit of measure	Piece	Piece
Lenght (mm)	877	1200
Width (mm)	379	800
Height (mm)	177	1130
Net weight (kg)	5.26	63.12
Gross weight (kg)	5.26	81.32