

Transition joint with screw connectors  
from belted cables / H-Type cables to three 1-core polymeric cables

Hybrid transition joints CHMPRSV3-1 for transition to three 1-core polymericinsulated cables, are suitable for belted cables and H-Type cables up to 17.5 kV. With screw connectors.



Product description

Article name	CHMPRSV3-1 17kV 70-150
Article number	265205

Characteristics

- Reliable stress control due to flexible silicone stress control elements
- Wide cross-section range
- Quick, safe and easy assembly
- Suitable for a wide range of applications due to integrated screw connector
- Ready for immediate operation

Applications

- Indoor
- Outdoor
- Underground
- Water
- Installation ducts
- Ductwork

↓

L

pos.	numeration	descriptions
1	18kg	Longue 2200 mm

	creation / date :	révision / numéro :	détails en lb / en lb :	
created :	22.12.2021	by :	note made in the past / not used as a note	
checked :	22.12.2021	by :	application / serial number :	quantity / s / lbs :
made in :	22.12.2021	total :	265205	pld
/// BBC			no in drawing / description :	
<b>CELLPACK</b>			<b>CHAMP3V3-1.17kW 70-150</b>	
Electrical Products			exam location / lbs in lbs :	
			<b>CEP0146 265205</b>	
			other / s / lbs :	
			1	

↑

Article name	CHMPRSV3-1 17kV 70-150
Article number	265205
Voltage levels	U0/U (Um) 6/10 (12) kV - 8,7/15 (17,5) kV
Test standards	DIN VDE 0278-629-2
Length L	1200 mm
Diameter over core insulation after removal of the outer conductive layer min	17.3 mm
Nominal cross section 12 kV min	95 mm <sup>2</sup>
Nominal cross section 12 kV max	150 mm <sup>2</sup>
Nominal cross section 17,5 kV min	70 mm <sup>2</sup>
Nominal cross section 17.5 kV max	150 mm <sup>2</sup>

## Logistics data

Article name	CHMPRSV3-1 17kV 70-150
Article number	265205
Delivery scope	Spreader cap
	Thick wall heat shrinkable outer tube with hot melt adhesive
	Oil barrier tubing
	Silicone field control elements
	Earthing wire
	Heat shrinkable tubes
	Copper braid tape
	Assembly material
	Screw connector for copper-wire screen
	Pressure spring
	Field control filling tape (blue)
	Sealing tape
	Fire protection wrapping
	Innovative screw connector with conductive cover
	Assembly instructions
Shelf life description	Unlimited shelf life
Country of origin	Germany
Customs tariff number	39269097
EAN/GTIN	4010311144764

## Packaging data

Alternative unit of measure	Carton	Pal. OW
Base quantity	1	12
Base unit of measure	Piece	Piece
Lenght (mm)	865	1200
Width (mm)	369	800
Height (mm)	170	1130
Net weight (kg)	6.165	73.98
Gross weight (kg)	6.165	92.18