

1-core straight-through joint
with screw connector for 1-core polymeric cables

Hybrid straight-through joints CHMSV are suitable for all 1-core polymeric-insulated cables (PVC, PE, XLPE, EPR). They allow the connection of cables with different cross sections and conductor materials even with different cable designs concerning the semi-conductive layer (graphite-coated, removable or strippable) and screen design (copper wire or tape screen). With screw connector.




Product description

Article name	CHMSV 17kV 70-150
Article number	258136
Notes	Can be used also for cables Um = 7,2 kV, then the minimum diameter over conductor insulation has to be checked. Straight-through joints with larger cross-section available on request.

Characteristics
Reliable stress control due to flexible silicone stress control elements
For both copper and aluminium conductors
For all cables with copper wire or tape screen
Wide conductor and cross-section range
Quick, safe and easy assembly
Ready for immediate operation
Suitable for a wide range of applications due to integrated screw connector

Applications
Indoor
Outdoor
Underground
Water
Installation ducts
Ductwork

Technical data



Article name	CHMSV 17kV 70-150
Article number	258136
Voltage levels	U0/U (Um) 8,7/15 (17,5) kV
Test standards	CENELEC HD 629.1
Length L	600 mm
Diameter over core insulation after removal of the outer conductive layer min	18 mm
Nominal cross section 17,5 kV min	70 mm ²
Nominal cross section 17,5 kV max	150 mm ²

Logistics data

Article name	CHMSV 17kV 70-150
Article number	258136
Delivery scope	Thick wall heat shrinkable insulation tubes
	Thick wall heat shrinkable outer tube with hot melt adhesive
	Silicone field control elements
	Copper braid tube
	Pressure springs
	Innovative screw connector with conductive cover
	Field control filling tape (blue)
	Assembly material
	Assembly instructions
Shelf life description	Unlimited shelf life
Country of origin	Germany
Customs tariff number	39269097
EAN/GTIN	4010311139715

Packaging data

Packaging type	Carton	Pal. OW
Content quantity	1	42
Unit of measure	Piece	Piece
Length (mm)	730	1200
Width (mm)	165	800
Height (mm)	157	1130
Net weight (kg)	1.213	50.946
Gross weight (kg)	1.213	69.146