

1-core straight-through joint
with screw connector for 1-core polymeric cables

Hybrid straight-through joints CHMSV are suitable for all 1-core polymeric-insulated cables (PVC, PE, XLPE, EPR). They allow the connection of cables with different cross sections and conductor materials even with different cable designs concerning the semi-conductive layer (graphite-coated, removable or strippable) and screen design (copper wire or tape screen). With screw connector.



Product description

Article name	CHMSV 24kV 240-400
Article number	258143
Notes	Can be used also for cables Um = 7,2 kV, then the minimum diameter over conductor insulation has to be checked. Straight-through joints with larger cross-section available on request.

Characteristics

Reliable stress control due to flexible silicone stress control elements
For both copper and aluminium conductors
For all cables with copper wire or tape screen
Wide conductor and cross-section range
Quick, safe and easy assembly
Ready for immediate operation
Suitable for a wide range of applications due to integrated screw connector

Applications

Indoor
Outdoor
Underground
Water
Installation ducts
Ductwork

Technical drawing of a cable with dimensions and a table of specifications.

Dimensions:

- Length: 1000 mm
- Outer diameter: 12.5 mm
- Inner diameter: 10.5 mm
- Thickness: 1.0 mm

Description / Description		Value / Valeur	Unit / Unité
Material / Matériau	Material / Matériau	Material / Matériau	Material / Matériau
Color / Couleur	Color / Couleur	Color / Couleur	Color / Couleur
Weight / Poids	Weight / Poids	Weight / Poids	Weight / Poids
Length / Longueur	Length / Longueur	Length / Longueur	Length / Longueur
Outer diameter / Diamètre extérieur	Outer diameter / Diamètre extérieur	Outer diameter / Diamètre extérieur	Outer diameter / Diamètre extérieur
Inner diameter / Diamètre intérieur	Inner diameter / Diamètre intérieur	Inner diameter / Diamètre intérieur	Inner diameter / Diamètre intérieur
Thickness / Épaisseur	Thickness / Épaisseur	Thickness / Épaisseur	Thickness / Épaisseur

Technical Data Sheet

Logistics data

Article name	CHMSV 24kV 240-400
Article number	258143
Delivery scope	Thick wall heat shrinkable insulation tubes
	Thick wall heat shrinkable outer tube with hot melt adhesive
	Silicone field control elements
	Copper braid tube
	Pressure springs
	Innovative screw connector with conductive cover
	Field control filling tape (blue)
	Assembly material
	Assembly instructions
Shelf life description	Unlimited shelf life
Country of origin	Germany
Customs tariff number	39269097
EAN/GTIN	4010311139784

Packaging data

Alternative unit of measure	Carton	Pal. EU
Base quantity	1	25
Base unit of measure	Piece	Piece
Length (mm)	725	1200
Width (mm)	233	800
Height (mm)	187	1130
Net weight (kg)	2.478	61.95
Gross weight (kg)	2.478	90.95