

Two-component gel based on silicon

to protect electrical components and LEDs

Sealing, high-transparent two-component sealing compound for a reliable protection to electrical components. Suitable for opto-electronic applications like e.g. sealing of LEDs and lighting installations.



Product description

Article name	CLEAR GEL 350
Article number	364034

Characteristics

Permanently high transparent

Favourable flow properties

Application-oriented variants

Non-labelled and non-toxic

Vibration damping

Removable

Flexible

Halogen-free

UV rays stable

Seals and protects all electrical installations

Applications

Indoor areas (also with high humidity levels)

Outdoor

Branch and connection boxes

Protection against moisture (IP 68 protection class in a suitable box)

For electrical systems up to 1 kV

Technical data

Article name	CLEAR GEL 350
Article number	364034
Content	350 ml
Viscosity (23 °C)	1000 mPas
Viscosity (associated standard)	ISO 2555
Processing time (pot life) (23 °C)	15 minutes
Processing time (pot life) (23 °C) (associated standard)	IEC 60684-2
Density	0.97 g/cm ³
Mixing ratio	1 : 1
Working temperature min	15 °C
Working temperature max	30 °C
Heat resistance min	-40 °C
Heat resistance max	150 °C
Specific volume resistivity	≥ 2 x 10 ¹⁴ Ω cm
Specific volume resistivity (associated standard)	HD 429
Dielectric strength	≥ 15 kV/mm
Dielectric strength (associated standard)	IEC 60243-1

Logistics data

Article name	CLEAR GEL 350
Article number	364034
Delivery scope	CLEAR GEL component A and component B in two-chamber bags
Shelf life	24 Month
Storage temperatur max	40 °C
Storage temperatur min	0 °C
Country of origin	China
Customs tariff number	39100000
EAN/GTIN	4010311177632

Packaging data

Packaging type	Case	Pal. OW
Content quantity	1	240
Unit of measure	Piece	Piece
Lenght (mm)	228	1200
Width (mm)	185	800
Height (mm)	33	550
Net weight (kg)	0.404	96.96
Gross weight (kg)	0.404	96.96