

Branch clamp

for low voltage

Branch clamp for aluminium sector shaped conductors. Suitable for 3- or 4-core cables with PVC, XLPE (VPE) EPR insulation.



Product description

Article name	Branch clamp 3x95/50-120/50
Article number	126196

Characteristics

Contact screws can be accessed from the side or from above

No stripping of wires

Can be installed / operated while under voltage

Safe and easy to handle

Applications

RM (class 2), SE (class 1) according to DIN EN/IEC 60228 (VDE 0295)

Technical data

Article name	Branch clamp 3x95/50-120/50
Article number	126196
Materials	Blank aluminium
Cross section Cu/RM min	95 mm ²
Cross section Cu/RM max	120 mm ²
Cross section Al/SE	150 mm ²
Cross section Branch cable min	16 mm ²
Cross section Branch cable max	50 mm ²
Width across flat 1	6 mm
Width across flat 2	5 mm
Diameter D	87 mm
Number of conductors	3 Pieces

Logistics data

Article name	Branch clamp 3x95/50-120/50
Article number	126196
Delivery scope	Branch clamp
Country of origin	Germany
Customs tariff number	85369010
EAN/GTIN	4010311048741

Packaging data

Alternative unit of measure	Bag1	Carton
Base quantity	1	5
Base unit of measure	Piece	Piece
Lenght (mm)	170	195
Width (mm)	100	155
Height (mm)	50	115
Net weight (kg)	0.435	2.175
Gross weight (kg)	0.435	2.475