

T-shaped separable coupling connector

for polymeric cables for separable connector type CTS

Cellplux T-shaped separable coupling connectors CTKS are suitable for connecting all polymeric-insulated 1-core cables VPE, (H)EPR), with different types of semi-conductive layers (graphite-coated or strippable) and screen design (wire or tape screen) to the back of T-shaped separable connectors type CTS.




Product description

Article name	CTKS 630A 36kV 150-240
Article number	257582
Notes	Separable connectors for alternative cross-sections and for class 5 conductors on request
Optional accessory	EGA earthing kit for cables with tape screen (see Connecting technology)

Characteristics	Applications
With capacitive measuring point for voltage checking	Indoor
Suitable for various cone voltage sensors	Outdoor
Routine tests (AC test, PD measurement, X-ray control)	
Outer semi-conductive layer made of semi-conductive EPDM provides protection from exposed electrical parts	
Cable sheath insulation fault test may be performed while under voltage	
For both copper and aluminium conductors	
Quick, safe and easy assembly	
Suitable for a wide range of applications due to integrated screw cable lug	

Technical data



Article name	CTKS 630A 36kV 150-240
Article number	257582
Voltage levels	U0/U (Um) 6/10 (12) kV - 19/33 (36) kV
	U0/U (Um) 12/20 (24) kV - 19/33 (36) kV
Test standards	CENELEC HD 629.1
Length L	310 mm
Width B	85 mm
Height H	250 mm
Diameter over core insulation after removal of the outer conductive layer min	30.8 mm
Diameter over core insulation after removal of the outer conductive layer max	37.6 mm
Nominal cross section 24 kV min	240 mm²
Nominal cross section 24 kV max	240 mm²
Nominal cross section 36 kV min	150 mm²
Nominal cross section 36 kV max	240 mm²

Logistics data

Article name	CTKS 630A 36kV 150-240
Article number	257582
Delivery scope	Set of 3 separable coupling connectors
	Silicone field control elements
	Earthing set
	Screw cable lugs for main conductor
	Assembly material
	Assembly instructions
Shelf life description	Unlimited shelf life
Storage temperatur max	50 °C
Storage temperatur min	0 °C
Country of origin	Germany
Customs tariff number	85479000
EAN/GTIN	4010311139227

Packaging data

Alternative unit of measure	Carton	Pal. OW
Base quantity	1	32
Base unit of measure	Piece	Piece
Lenght (mm)	379	1200
Width (mm)	289	800
Height (mm)	235	1130
Net weight (kg)	6.046	193.472
Gross weight (kg)	6.046	211.672