

Compression cable lug Al

longitudinally sealed for low and medium voltage

Cable lug (hexagonally compressed) for aluminium conductors, suitable for indoor and outdoor cable terminations.



Product description

Article name	DK-AL-LD 150/12
Article number	194937
Notes	To be used with suitable crimping tool with DIN inserts

Applications

Cable lug for aluminium conductor RM/SM (Class 2), RE and SE (Class 1) according to DIN EN 60228 (VDE 0295)

Technical data



Article name	DK-AL-LD 150/12
Article number	194937
Test standards	DIN 46329
Materials	Blank aluminium
Length L	90 mm
Width B	30 mm
Diameter D1	16.3 mm
Diameter D2	13 mm
Diameter D3	25 mm
Nominal cross section RM/SM	150 mm ²
Nominal cross section SE	185 mm ²
Press die code K	25 mm
Length A	60 mm

Logistics data

Article name	DK-AL-LD 150/12
Article number	194937
Delivery scope	Compression cable lug
Country of origin	Poland
Customs tariff number	85369010
EAN/GTIN	4010311052939

Packaging data

Packaging type	Bag1	Carton
Content quantity	1	50
Unit of measure	Piece	Piece
Lenght (mm)	110	290
Width (mm)	30	195
Height (mm)	25	145
Net weight (kg)	0.088	4.4
Gross weight (kg)	0.088	4.7