

Compression cable lug Cu  
for low and medium voltage

Cable lug (hexagonally compressed) for copper conductors, suitable for indoor cable terminations.



Product description

Article name	DK-CU-V 150/16
Article number	126082
Notes	To be used with suitable crimping tool with DIN inserts

Applications

Cable lug recommended for copper conductors RM/SM (class 2) according to DIN EN 60228 (VDE 0295)

## Technical data



Article name	DK-CU-V 150/16
Article number	126082
Test standards	DIN 46235
	IEC 61238
Materials	Copper tin-plated
Length L	78 mm
Width B	34 mm
Diameter D1	17 mm
Diameter D2	17 mm
Diameter D3	23.5 mm
Nominal cross section min	150 mm <sup>2</sup>
Press die code K	22 mm
Length A	40 mm

## Logistics data

Article name	DK-CU-V 150/16
Article number	126082
Delivery scope	Compression cable lug
Country of origin	Poland
Customs tariff number	85369010
EAN/GTIN	4010311052571

## Packaging data

Packaging type	Bag1	Carton
Content quantity	1	50
Unit of measure	Piece	Piece
Lenght (mm)	96	195
Width (mm)	31	145
Height (mm)	22	145
Net weight (kg)	0.16	8
Gross weight (kg)	0.16	8.3