

Compression cable lug Cu

for low and medium voltage

Cable lug (hexagonally compressed) for copper conductors, suitable for indoor cable terminations.



Product description

Article name	DK-CU-V 300/14
Article number	126093
Notes	To be used with suitable crimping tool with DIN inserts

Applications

Cable lug recommended for copper conductors RM/SM (class 2) according to DIN EN 60228 (VDE 0295)

Technical data



Article name	DK-CU-V 300/14
Article number	126093
Test standards	DIN 46235
	IEC 61238
Materials	Copper tin-plated
Length L	100 mm
Width B	48 mm
Diameter D1	24.5 mm
Diameter D2	15 mm
Diameter D3	32 mm
Nominal cross section min	300 mm ²
Press die code K	32 mm
Length A	52 mm

Logistics data

Article name	DK-CU-V 300/14
Article number	126093
Delivery scope	Compression cable lug
Country of origin	Poland
Customs tariff number	85369010
EAN/GTIN	4010311052625

Packaging data

Packaging type	Bag1	Carton
Content quantity	1	25
Unit of measure	Piece	Piece
Length (mm)	118	195
Width (mm)	41	145
Height (mm)	30	145
Net weight (kg)	0.326	8.15
Gross weight (kg)	0.326	8.45