

Heat shrinkable crimp connector  
insulated with heat shrinkable tube with adhesive

Durable and reliable connector for application in areas under extreme conditions. Hot melt adhesive completely seals the connection area.



Product description

Article name	DR-L 2
Article number	456336
Notes	For a proper conductor/connector contact, use a suitable crimping tool.

Characteristics
100 % waterproof
Superior electrical properties
High mechanical strength

Applications
Indoor

## Technical data

Article name	DR-L 2
Article number	456336
Selection Note	20 Heat shrinkable crimp connectors
Length L	55 mm
Colours	blue
Nominal cross section min	1.5 mm <sup>2</sup>
Nominal cross section max	2.5 mm <sup>2</sup>
Water absorption max	0.5 %
Voltage max	600 V
Tensile strength	10.4 MPa
Heat resistance (168 h at 175 °C)	No fracturing
Heat shock (4 h at 225 °C)	No fracturing
Temperature range min	-40 °C
Temperature range max	105 °C
Shrinkage temperature	> 150 °C
Corrosion	none

## Logistics data

Article name	DR-L 2
Article number	456336
Delivery scope	20 Heat shrinkable crimp connectors
Country of origin	China
Customs tariff number	85369010
EAN/GTIN	4010311199597

## Packaging data

Alternative unit of measure	Bag	Carton
Base quantity	20	1000
Base unit of measure	Piece	Piece
Length (mm)	145	220
Width (mm)	70	160
Height (mm)	7	90
Net weight (kg)	0.06	3
Gross weight (kg)	0.062	3.3