

Compression connector Cu
according to DIN 46267 with separator for low voltage

Strain-relieving connector (hexagonally compressed)
with a separator for copper conductors, suitable for
joints.




Product description

Article name	DVZ-CU-V-LD 70
Article number	125901
Notes	To be used with suitable crimping tool with DIN inserts

Applications
Especially for transition joints and pot end joints
Connector for RM/SM (Class 2) copper conductors according to DIN EN 60228 (VDE 0295)

Technical data



Article name	DVZ-CU-V-LD 70
Article number	125901
Test standards	DIN 46267-1
Materials	Copper tin-plated
Length L	56 mm
Diameter D1	11.5 mm
Nominal cross section min	70 mm ²
Nominal cross section max	70 mm ²
Press die code K	16 mm

Logistics data

Article name	DVZ-CU-V-LD 70
Article number	125901
Delivery scope	Compression connectors
Country of origin	Germany
Customs tariff number	85369010
EAN/GTIN	4010311053257

Packaging data

Packaging type	Bag1	Case
Content quantity	1	25
Unit of measure	Piece	Piece
Lenght (mm)	55	140
Width (mm)	18	110
Height (mm)	18	60
Net weight (kg)	0.057	1.425
Gross weight (kg)	0.057	1.725