

Earthing set for cable terminations
for cables with tape screen and/or armouring for cable terminations

EGA earthing set for cable terminations for 1-core cables with copper tape or aluminium screen and for unarmoured 3-core cables. Kit components: 3 flat-rolled copper earth braids and 3 pressure springs.



Product description

Article name	EGA 16-2/700mm
Article number	375286
Notes	Additional pressure springs RF (ZR1/ZR2) for armoured cables to be ordered separately (see Accessories).

Characteristics

- Quick, safe and easy assembly
- Superior electrical properties
- High mechanical strength

Applications

- Earthing continuity and earth bonding
- For cast resin, heat shrinkable and slip-on cable accessories
- Enables solder-free electrical connection of metal cable components (screen, armouring, metal sheath)

Technical data

Article name	EGA 16-2/700mm
Article number	375286
Pressure spring type	RF2
Diameter hole Copper earth braid	8.5 mm
Nominal cross section Copper earth braid	16 mm ²
Additional pressure spring ZR1	RF3
Additional pressure spring ZR2	RF5
Length L	700 mm
Nominal cross section 7,2 kV min	150 mm ²
Nominal cross section 7,2 kV max	150 mm ²
Nominal cross section 12 kV min	120 mm ²
Nominal cross section 12 kV max	120 mm ²
Nominal cross section 17,5 kV min	70 mm ²
Nominal cross section 17,5 kV max	70 mm ²
Nominal cross section 24 kV min	50 mm ²
Nominal cross section 24 kV max	50 mm ²

Logistics data

Article name	EGA 16-2/700mm
Article number	375286
Delivery scope	1 Set for 3 phases: Copper braid earth tapes, pressure springs RF
Country of origin	Germany
Customs tariff number	85444995
EAN/GTIN	4010311185996

Packaging data

Alternative unit of measure	Bag1	Carton
Base quantity	1	50
Base unit of measure	Piece	Piece
Lenght (mm)	300	585
Width (mm)	140	400
Height (mm)	20	330
Net weight (kg)	0.039	1.95
Gross weight (kg)	0.039	2.25