

Protective agent
for protection of electrical equipment

Specially for preventing and eliminating defects in electrical installations caused by moisture, corrosion, contamination or friction. Low surface tension and excellent creeping properties even in hard-to-reach places, penetrates into the finest crevices and thus unfolds its effectiveness.



Product description

Article name	ELECTRO 2-26 Spray
Article number	124045

Characteristics
Lubricates and permeates

Applications
Corrosion protection
Oxidation protection
Protection against flying sparks
Protection against leakage current
Short-circuit protection
Maintenance and protection of electrical equipment
Improves drag coefficient
Expels and provides sealing against moisture

Technical data

Article name	ELECTRO 2-26 Spray
Article number	124045
Content	0.4 l
Colours	transparent color
Viscosity (40 °C)	30 cP
Flash point	105 °C
Density	0.8 g/cm ³
Dielectric strength	150 kV/mm

Logistics data

Article name	ELECTRO 2-26 Spray
Article number	124045
Delivery scope	Protective agent
Shelf life	24 Month
Storage temperatur max	25 °C
Storage temperatur min	20 °C
Country of origin	France
Customs tariff number	34039900
EAN/GTIN	4010311049007

Packaging data

Packaging type	Tin	Carton	Pal. OW
Content quantity	1	12	120
Unit of measure	Piece	Piece	Piece
Lenght (mm)	65	276	1200
Width (mm)	65	219	800
Height (mm)	200	212	550
Net weight (kg)	0.434	5.208	52.08
Gross weight (kg)	0.434	5.219	70.28