

## Protective agent

for protection of electrical equipment

Specially for preventing and eliminating defects in electrical installations caused by moisture, corrosion, contamination or friction. Low surface tension and excellent creeping properties even in hard-to-reach places, penetrates into the finest crevices and thus unfolds its effectiveness.



## Product description

Article name	ELECTRO 2-26 Spray
Article number	124045

### Characteristics

Lubricates and permeates

### Applications

- Corrosion protection
- Oxidation protection
- Protection against flying sparks
- Protection against leakage current
- Short-circuit protection
- Maintenance and protection of electrical equipment
- Improves drag coefficient
- Expels and provides sealing against moisture

## Technical data

Article name	ELECTRO 2-26 Spray
Article number	124045
Content	0.4 l
Colours	transparent color
Viscosity (40 °C)	30 cP
Flash point	105 °C
Density	0.8 g/cm <sup>3</sup>
Dielectric strength	150 kV/mm

## Logistics data

Article name	ELECTRO 2-26 Spray
Article number	124045
Delivery scope	Protective agent (Spray)
Shelf life	24 Month
Storage temperatur max	25 °C
Storage temperatur min	20 °C
Country of origin	France
Customs tariff number	34039900
EAN/GTIN	4010311049007

## Packaging data

Alternative unit of measure	Tin	Carton	Pal. OW
Base quantity	1	12	120
Base unit of measure	Piece	Piece	Piece
Lenght (mm)	65	276	1200
Width (mm)	65	219	800
Height (mm)	200	212	550
Net weight (kg)	0.434	5.208	52.08
Gross weight (kg)	0.434	5.219	70.28