

Protective agent
for protection of electrical equipment

Specially for preventing and eliminating defects in electrical installations caused by moisture, corrosion, contamination or friction. Low surface tension and excellent creeping properties even in hard-to-reach places, penetrates into the finest crevices and thus unfolds its effectiveness.



Product description

Article name	ELECTRO 2-26 Canister
Article number	124046

Characteristics
Lubricates and permeates

Applications
Corrosion protection
Oxidation protection
Protection against flying sparks
Protection against leakage current
Short-circuit protection
Maintenance and protection of electrical equipment
Improves drag coefficient
Expels and provides sealing against moisture

Technical data

Article name	ELECTRO 2-26 Canister
Article number	124046
Content	5 l
Colours	transparent color
Viscosity (40 °C)	30 cP
Flash point	105 °C
Density	0.8 g/cm ³
Dielectric strength	150 kV/mm

Logistics data

Article name	ELECTRO 2-26 Canister
Article number	124046
Delivery scope	Protective agent
Shelf life	24 Month
Storage temperatur max	25 °C
Storage temperatur min	20 °C
Country of origin	France
Customs tariff number	34039900
EAN/GTIN	4010311049014

Packaging data

Alternative unit of measure	Canister	Pal. OW
Base quantity	1	12
Base unit of measure	Piece	Piece
Lenght (mm)	275	1200
Width (mm)	139	800
Height (mm)	322	550
Net weight (kg)	4.721	56.652
Gross weight (kg)	4.721	74.852