

Two-component PUR cast resin

reduced hazard-class, without training

Cast resin GG is a special development to fulfill reduced hazard-classification. It's labelling identification, according to the CLP-Regulation (EC) No. 1272/2008, does not contain the H351 statement. The cast resin GG has similar properties as the known polyurethane cast resins. Cast resin GG is suitable for low voltage polymeric-insulated and mass-impregnated paper cables up to 1 kV.



Product description

Article name	GG 1000
Article number	353818
Notes	Other sizes available on request. Diisocyanates training is not required.

Characteristics
Favourable flow properties
High hydrolysis resistance
Stabilized against UV rays
Halogen-free
Resistant to alkaline earth elements
Not harmful to the environment
Flexibility ensures mechanical stress absorption
No fracturing under electrical stress
Low hardening temperature
Low hardening temperature
Low hardening temperature

Technical data

Article name	GG 1000
Article number	353818
Test standards	DIN VDE 0278-631-1
Content	1000 ml
Flash point of cast resin component (open cup)	> 200 °C
Flash point of reactant (open cup)	> 200 °C
Processing time (pot life) 300 ml mixture 5 °C	68 minutes
Processing time (pot life) 300 ml mixture 23 °C	24 minutes
Processing time (pot life) 300 ml mixture 35 °C	15 minutes
Reaction temperature max	60 °C
Total volume shrinkage during curing	< 6 %
Impact strength	> 10 kJ/m ²
Hardness	30 Shore D
Density	1.32 g/cm ³
Density cured casting compound (associated standard)	ISO 1183-1
Operation temperature min.	-40 °C
Operation temperature max.	90 °C

Logistics data

Article name	GG 1000
Article number	353818
Delivery scope	Cast resin
	Packed in practical and easy-to-use two-chamber bags
Shelf life	24 Month
Shelf life description	In aluminium bag
Storage temperatur max	35 °C
Storage temperatur min	15 °C
Country of origin	Germany
Customs tariff number	39095090
EAN/GTIN	4010311171166

Packaging data

Packaging type	Case	Pal. OW
Content quantity	1	72
Unit of measure	Piece	Piece
Lenght (mm)	341	1200
Width (mm)	186	800
Height (mm)	39	550
Net weight (kg)	1.465	105.48
Gross weight (kg)	1.465	123.68