

Cable ties

Standard

Cable ties for quick and secure bundling, standard version.



Product description

Article name	KS 4.5/200
Article number	146426
Notes	Under standard conditions 9,81 N correspond to 1 kg

Characteristics

Smooth, rounded edges for safe and easy handling and assembly

Internal gearing and rounded-off end to facilitate take-up, insertion and tightening

Resistant to alkaline earth elements

Resistant to mould and oil

Stabilized against UV rays

Resistant to dilute acids and alkalis

Halogen-free

Flame retardant

Silicone free

Applications

Bundling

Affixing

## Technical data

Article name	KS 4.5/200
Article number	146426
Test standards	EN 62275
Materials	Polyamide 6.6
Holding force min	216 N
Bundle diameter max	51 mm
Length L	200 mm
Width B	4.5 mm
Colours	black
Flammability rating	UL 94 V2
Mounting temperature min	-5 °C
Mounting temperature max	40 °C
Operation temperature min	-40 °C
Operation temperature max	85 °C

## Logistics data

Article name	KS 4.5/200
Article number	146426
Delivery scope	100 Cable ties
Shelf life description	At 50 % relative humidity After opening the bag, must be used rapidly
Storage temperatur max	23 °C
Country of origin	Italy
Customs tariff number	39269097
EAN/GTIN	4010311006499

## Packaging data

Alternative unit of measure	Bag	Carton
Base quantity	100	10000
Base unit of measure	Piece	Piece
Lenght (mm)	220	600
Width (mm)	130	400
Height (mm)	30	310
Net weight (kg)	0.1	10
Gross weight (kg)	0.105	10.3