

Cable ties

Standard

Cable ties for quick and secure bundling, standard version.



Product description

Article name	KS 4.5/360
Article number	146435
Notes	Under standard conditions 9,81 N correspond to 1 kg

Characteristics	Applications
Smooth, rounded edges for safe and easy handling and assembly	Bundling
Internal gearing and rounded-off end to facilitate take-up, insertion and tightening	Affixing
Resistant to alkaline earth elements	
Resistant to mould and oil	
Stabilized against UV rays	
Resistant to dilute acids and alkalis	
Halogen-free	
Flame retardant	
Silicone free	

## Technical data

Article name	KS 4.5/360
Article number	146435
Test standards	EN 62275
Materials	Polyamide 6.6
Holding force min	216 N
Bundle diameter max	101 mm
Length L	360 mm
Width B	4.5 mm
Colours	natural color
Flammability rating	UL 94 V2
Mounting temperature min	-5 °C
Mounting temperature max	40 °C
Operation temperature min.	-40 °C
Operation temperature max.	85 °C

## Logistics data

Article name	KS 4.5/360
Article number	146435
Delivery scope	Cable ties
Shelf life description	At 50 % relative humidity After opening the bag, must be used rapidly
Storage temperatur max	23 °C
Country of origin	Italy
Customs tariff number	39269097
EAN/GTIN	4010311006789

## Packaging data

Packaging type	Bag	Carton	Pal. OW
Content quantity	100	8000	96000
Unit of measure	Piece	Piece	Piece
Lenght (mm)	420	600	1200
Width (mm)	95	400	800
Height (mm)	35	310	1200
Net weight (kg)	0.2	16	192
Gross weight (kg)	0.205	16.3	210.2