

Cable ties

Standard

Cable ties for quick and secure bundling, standard version.



Product description

Article name	KS 7.5/750
Article number	146443
Notes	Under standard conditions 9,81 N correspond to 1 kg

Characteristics

Smooth, rounded edges for safe and easy handling and assembly

Internal gearing and rounded-off end to facilitate take-up, insertion and tightening

Resistant to alkaline earth elements

Resistant to mould and oil

Stabilized against UV rays

Resistant to dilute acids and alkalis

Halogen-free

Flame retardant

Silicone free

Applications

Bundling

Affixing

Technical data

Article name	KS 7.5/750
Article number	146443
Test standards	EN 62275
Materials	Polyamide 6.6
Holding force min	588 N
Bundle diameter max	220 mm
Length L	750 mm
Width B	7.5 mm
Colours	natural color
Flammability rating	UL 94 V2
Mounting temperature min	-5 °C
Mounting temperature max	40 °C
Operation temperature min	-40 °C
Operation temperature max	85 °C

Logistics data

Article name	KS 7.5/750
Article number	146443
Delivery scope	100 Cable ties
Shelf life description	At 50 % relative humidity
	After opening the bag, must be used rapidly
Storage temperatur max	23 °C
Country of origin	Italy
Customs tariff number	39269097
EAN/GTIN	4010311007083

Packaging data

Alternative unit of measure	Bag	Carton	Pal. OW
Base quantity	100	1500	18000
Base unit of measure	Piece	Piece	Piece
Lenght (mm)	820	800	1200
Width (mm)	155	300	800
Height (mm)	30	300	1200
Net weight (kg)	1.2	18	216
Gross weight (kg)	1.205	18.3	234.2