

Cable ties

Standard

Cable ties for quick and secure bundling, standard version.



Product description

Article name	KS 12.5/500
Article number	146445
Notes	Under standard conditions 9,81 N correspond to 1 kg

Characteristics

Smooth, rounded edges for safe and easy handling and assembly

Internal gearing and rounded-off end to facilitate take-up, insertion and tightening

Resistant to alkaline earth elements

Resistant to mould and oil

Stabilized against UV rays

Resistant to dilute acids and alkalis

Halogen-free

Highly flammable

Silicone free

Applications

Bundling

Affixing

Technical data

Article name	KS 12.5/500
Article number	146445
Test standards	EN 62275
Materials	Polyamide 6.6
Holding force min	1140 N
Bundle diameter max	140 mm
Length L	500 mm
Width B	12.5 mm
Colours	natural color
Flammability rating	UL 94 V2
Mounting temperature min	-5 °C
Mounting temperature max	40 °C
Operation temperature min.	-40 °C
Operation temperature max.	85 °C

Logistics data

Article name	KS 12.5/500
Article number	146445
Delivery scope	Cable ties
Shelf life description	At 50 % relative humidity After opening the bag, must be used rapidly
Storage temperatur max	23 °C
Country of origin	Italy
Customs tariff number	39269097
EAN/GTIN	4010311007182

Packaging data

Packaging type	Bag	Carton	Pal. OW
Content quantity	50	1000	12000
Unit of measure	Piece	Piece	Piece
Lenght (mm)	670	600	1200
Width (mm)	315	400	800
Height (mm)	320	310	1200
Net weight (kg)	0.7	14	168
Gross weight (kg)	0.705	14.3	186.2