

## Cable ties

### Standard

Cable ties for quick and secure bundling, standard version.



### Product description

Article name	KS 12.5/1000
Article number	146446
Notes	Under standard conditions 9,81 N correspond to 1 kg

#### Characteristics

Smooth, rounded edges for safe and easy handling and assembly

Internal gearing and rounded-off end to facilitate take-up, insertion and tightening

Resistant to alkaline earth elements

Resistant to mould and oil

Stabilized against UV rays

Resistant to dilute acids and alkalis

Halogen-free

Flame retardant

Silicone free

#### Applications

Bundling

Affixing

## Technical data

Article name	KS 12.5/1000
Article number	146446
Test standards	EN 62275
Materials	Polyamide 6.6
Holding force min	1140 N
Bundle diameter max	300 mm
Length L	1000 mm
Width B	12.5 mm
Colours	black
Flammability rating	UL 94 V2
Mounting temperature min	-5 °C
Mounting temperature max	40 °C
Operation temperature min	-40 °C
Operation temperature max	85 °C

## Logistics data

Article name	KS 12.5/1000
Article number	146446
Delivery scope	50 Cable ties
Shelf life description	At 50 % relative humidity After opening the bag, must be used rapidly
Storage temperatur max	23 °C
Country of origin	Italy
Customs tariff number	39269097
EAN/GTIN	4010311007199

## Packaging data

Alternative unit of measure	Bag	Carton	Pal. OW
Base quantity	50	1000	12000
Base unit of measure	Piece	Piece	Piece
Lenght (mm)	950	800	1200
Width (mm)	112	300	800
Height (mm)	40	300	1200
Net weight (kg)	1.3	26	312
Gross weight (kg)	1.305	26.3	330.2