

Putty/sealing compound  
for sealing of wall ducts

Sealant for sealing cable and pipe openings in areas  
in contact with the ground.



Product description

Article name	LG 250
Article number	125198
Notes	Other sizes available on request.
Optional accessory	Centring aid KZ (see Accessories)
	Cleaner UNIVERSAL CLEANER 121 (see Accessories)

Characteristics

Removable
Halogen-free
Not harmful to the environment
Gas-tight and waterproof up to 1.5 bar
Flexible after hardening
Superior adhesion to metal, plastics (PVC, XLPE and PE), concrete, artificial and natural stone
Superior thermodynamic properties
Superior adhesion to metal, plastics (PVC, XLPE and PE), concrete, artificial and natural stone
Superior thermodynamic properties

Applications

Outdoor
Indoor
Underground
Water
Sealing of wall ducts

## Technical data

Article name	LG 250
Article number	125198
Content	250 ml
Flash point of cast resin component (open cup)	200 °C
Flash point of reactant (open cup)	200 °C
Processing time (pot life) 250 ml mixture 20 °C	15 minutes
Processing time (pot life) 250 ml mixture 35 °C	9 minutes
Reaction temperature max	60 °C
Hardness	80 Shore A
Density	1.1 g/cm <sup>3</sup>

## Logistics data

Article name	LG 250
Article number	125198
Delivery scope	Putty/sealing compound
	Spatula
	Assembly instructions
Shelf life	18 Month
Shelf life description	In aluminium bag
Storage temperatur max	35 °C
Storage temperatur min	15 °C
Country of origin	Germany
Customs tariff number	39095090
EAN/GTIN	4010311003832

## Packaging data

Packaging type	Case	Pal. OW
Content quantity	1	360
Unit of measure	Piece	Piece
Lenght (mm)	232	1200
Width (mm)	185	800
Height (mm)	32	770
Net weight (kg)	0.378	136.08
Gross weight (kg)	0.378	154.28