

Splice cassette system
for fibre optic cables

The splice cassette system offers the optimal solution when it comes to the management of fibre optic connections and the safe storage of spliced fibres. It can be used in a wide range of LAN, WAN and MAN applications in the fibre-to-the-home and industrial sectors. The system includes splice cassettes and components that can be reliably used in various applications. The splice cassettes ensure orderly storage and can be combined with each other as required.



Product description

Article name	LHS Shrink splice protection
Article number	146706
Notes	Recommended operating temperature range of -55 to +70 °C

Characteristics
Flange mount strain relief for fibre optic cables
Insertion opening for up to max. 12 glass fibres
Flame-retardant plastic housing
All current splice holders are interlockable (with anti-rotation protection)
Easy attachment of stranded conductors
Counter support bracket for easy insertion of glass fibres
The conductors can be easily redirected to other levels
Halogen-free
Mechanical strain relief

Applications
Compact joints
Coupler housing for joints or trays
Mechanical protection for spliced optical fibres
Drawer application (modular compartments), choice of stress relief bushing for easy assembly of pigtail
Vertical compartments for multifunctionality and flexibility
Where high performance fibre optic cabling and connections are required

Technical data

Article name	LHS Shrink splice protection
Article number	146706
Materials	Ethyl vinyl acetate insert Flexible heat shrinkable tube
Colours	transparent color

Logistics data

Article name	LHS Shrink splice protection
Article number	146706
Delivery scope	100 Shrink splice protections
Country of origin	Great Britain
Customs tariff number	39269097
EAN/GTIN	4010311020990

Packaging data

Packaging type	Bag
Content quantity	50
Unit of measure	Piece
Length (mm)	95
Width (mm)	95
Height (mm)	2
Net weight (kg)	0.05
Gross weight (kg)	0.055