

Cast resin straight-through joint
for polymeric cables and control cables and signal cables

Universally suitable for connecting polymeric cables or conductors insulated with PVC, PE, XLPE and EPR (e.g. N(A)YY, NYM, TT). With hydrolysis resistance PUR cast resin EG. Suitable for compression or screw connectors on copper and aluminium conductors.




Product description

Article name	M 0 EG
Article number	124293
Notes	Armour continuity kit for armoured cable available on request. The European Commission amended Annex XVII of the REACH Regulation (EC) (new number 74) with Regulation (EU) 2020/1149, which entered into force on 24 August 2020. In accordance with the new REACH Regulation, appropriate training will be required prior to the industrial or professional use of diisocyanates, adhesives and sealants as of 24 August 2023. All information regarding training materials and training courses is available on the ISOPA/ALIPA website https://www.safeusediisocyanates.eu/
Optional accessory	Cleaner UNIVERSAL CLEANER 121 (see Accessories) Shield continuity wire SVL (see Accessories) Connectors (see Connecting technology)

Characteristics
Compact dimensions
Splice area visible before casting
High-quality transparent shockproof plastic shell
Resistant to chemical agents
Stabilized against UV rays
Resistant to alkaline earth elements
Longitudinally and transversely watertight
High electrical insulating values
High mechanical strength
Ready for immediate operation
Quick, safe and easy assembly

Applications
Indoor
Outdoor
Underground
Water
Installation ducts

Technical data



Article name	M 0 EG
Article number	124293
Voltage levels	U0/U (Um) 0,6/1 (1,2) kV
Test standards	EN 50393
Length L	185 mm
Height H	37 mm
Diameter D	32 mm
Nominal cross section Polymeric cable unarmoured per conductor 1x max	25 mm ²
Nominal cross section Polymeric cable unarmoured per conductor 2x max	10 mm ²
Nominal cross section Polymeric cable unarmoured per conductor 3x max	6 mm ²
Nominal cross section Polymeric cable unarmoured per conductor 4x max	6 mm ²
Nominal cross section Polymeric cable unarmoured per conductor 5x max	4 mm ²
Diameter cable max	15 mm
Control and signal cable 0,75 mm ² Number of conductors	16 Pieces
Control and signal cable 1,5 mm ² Number of conductors	8 Pieces
Control and signal cable 0,4 mm Number of wire pairs min	6 Pieces
Control and signal cable 0,4 mm Number of wire pairs max	20 Pieces
Control and signal cable 0,6 mm Number of wire pairs min	6 Pieces
Control and signal cable 0,6 mm Number of wire pairs max	10 Pieces
Control and signal cable 0,8 mm Number of wire pairs min	6 Pieces
Control and signal cable 0,8 mm Number of wire pairs max	6 Pieces

Logistics data

Article name	M 0 EG
Article number	124293
Delivery scope	Fill and air-release funnel
	Hydrolysis resistance PUR cast resin EG
	Packed in practical and easy-to-use two-chamber bags
	Transparent plastic shell
	PVC insulation tape
	Protective gloves
	Assembly instructions
Shelf life	40 Month
Storage temperatur max	35 °C
Storage temperatur min	15 °C
Country of origin	Germany
Customs tariff number	39095090
EAN/GTIN	4010311000046

Packaging data

Packaging type	Case	Pal. EU
Content quantity	1	480
Unit of measure	Piece	Piece
Lenght (mm)	205	1200
Width (mm)	158	800
Height (mm)	49	1130
Net weight (kg)	0.336	161.28
Gross weight (kg)	0.336	190.28