

## Cast resin straight-through joint

for polymeric cables and control cables and signal cables

Universally suitable for connecting polymeric cables or conductors insulated with PVC, PE, XLPE and EPR (e.g. N(A)YY, NYM, TT). With hydrolysis resistance PUR cast resin EG. Suitable for compression or screw connectors on copper and aluminium conductors.




### Product description

Article name	M 1 EG
Article number	124294
Notes	Armour continuity kit for armoured cable available on request. The European Commission amended Annex XVII of the REACH Regulation (EC) (new number 74) with Regulation (EU) 2020/1149, which entered into force on 24 August 2020. In accordance with the new REACH Regulation, appropriate training will be required prior to the industrial or professional use of diisocyanates, adhesives and sealants as of 24 August 2023. All information regarding training materials and training courses is available on the ISOPA/ALIPA website <a href="https://www.safeusediisocyanates.eu/">https://www.safeusediisocyanates.eu/</a>
Optional accessory	Cleaner UNIVERSAL CLEANER 121 (see Accessories) Shield continuity wire SVL (see Accessories) Connectors (see Connecting technology)

Characteristics
Compact dimensions
Splice area visible before casting
High-quality transparent shockproof plastic shell
Resistant to chemical agents
Stabilized against UV rays
Resistant to alkaline earth elements
Longitudinally and transversely watertight
High electrical insulating values
High mechanical strength
Ready for immediate operation
Quick, safe and easy assembly

Applications
Indoor
Outdoor
Underground
Water
Installation ducts

## Technical data



Article name	M 1 EG
Article number	124294
Voltage levels	U0/U (Um) 0,6/1 (1,2) kV
Test standards	EN 50393
Length L	240 mm
Height H	45 mm
Diameter D	40 mm
Nominal cross section Polymeric cable unarmoured per conductor 1x max	95 mm <sup>2</sup>
Nominal cross section Polymeric cable unarmoured per conductor 2x max	25 mm <sup>2</sup>
Nominal cross section Polymeric cable unarmoured per conductor 3x max	16 mm <sup>2</sup>
Nominal cross section Polymeric cable unarmoured per conductor 4x max	16 mm <sup>2</sup>
Nominal cross section Polymeric cable unarmoured per conductor 5x max	10 mm <sup>2</sup>
Diameter cable max	22 mm
Nominal cross section Polymeric cable with concentric conductor per conductor 3x max	10 mm <sup>2</sup>
Control and signal cable 0,75 mm <sup>2</sup> Number of conductors	56 Pieces
Control and signal cable 1,5 mm <sup>2</sup> Number of conductors	21 Pieces
Control and signal cable 0,4 mm Number of wire pairs min	30 Pieces
Control and signal cable 0,4 mm Number of wire pairs max	70 Pieces
Control and signal cable 0,6 mm Number of wire pairs min	20 Pieces
Control and signal cable 0,6 mm Number of wire pairs max	30 Pieces
Control and signal cable 0,8 mm Number of wire pairs min	10 Pieces
Control and signal cable 0,8 mm Number of wire pairs max	20 Pieces

## Logistics data

Article name	M 1 EG
Article number	124294
Delivery scope	Fill and air-release funnel Hydrolysis resistance PUR cast resin EG Packed in practical and easy-to-use two-chamber bags Transparent plastic shell PVC insulation tape Protective gloves Assembly instructions
Shelf life	40 Month
Storage temperatur max	35 °C
Storage temperatur min	15 °C
Country of origin	Germany
Customs tariff number	39095090
EAN/GTIN	4010311000053

## Packaging data

Packaging type	Case	Pal. OW
Content quantity	1	256
Unit of measure	Piece	Piece
Lenght (mm)	277	1200
Width (mm)	193	800
Height (mm)	65	1130
Net weight (kg)	0.531	135.936
Gross weight (kg)	0.531	154.136