

Cast resin straight-through joint
for polymeric cables and control cables and signal cables

Universally suitable for connecting polymeric cables or conductors insulated with PVC, PE, XLPE and EPR (e.g. N(A)YY, NYM, TT). With hydrolysis resistance PUR cast resin GG. Suitable for compression or screw connectors on copper and aluminium conductors.



Product description

Article name	M 0 GG
Article number	353703
Notes	Armour continuity kit for armoured cable available on request.
Optional accessory	Cleaner UNIVERSAL CLEANER 121 (see Accessories)
	Shield continuity wire SVL (see Accessories)
	Connectors (see Connecting technology)


Characteristics

Compact dimensions
Splice area visible before casting
High-quality transparent shockproof plastic shell
Resistant to chemical agents
Stabilized against UV rays
Resistant to alkaline earth elements
Longitudinally and transversely watertight
High electrical insulating values
High mechanical strength
Ready for immediate operation
Quick, safe and easy assembly

Applications

Indoor
Outdoor
Underground
Water
Installation ducts

Technical data



Article name	M 0 GG
Article number	353703
Voltage levels	U0/U (Um) 0,6/1 (1,2) kV
Test standards	EN 50393
Length L	185 mm
Height H	37 mm
Diameter D	32 mm
Nominal cross section Polymeric cable unarmoured per conductor 1x max	25 mm ²
Nominal cross section Polymeric cable unarmoured per conductor 2x max	10 mm ²
Nominal cross section Polymeric cable unarmoured per conductor 3x max	6 mm ²
Nominal cross section Polymeric cable unarmoured per conductor 4x max	6 mm ²
Nominal cross section Polymeric cable unarmoured per conductor 5x max	4 mm ²
Diameter cable max	15 mm
Control and signal cable 0,75 mm ² Number of conductors	16 Pieces
Control and signal cable 1,5 mm ² Number of conductors	8 Pieces
Control and signal cable 0,4 mm Number of wire pairs min	6 Pieces
Control and signal cable 0,4 mm Number of wire pairs max	20 Pieces
Control and signal cable 0,6 mm Number of wire pairs min	6 Pieces
Control and signal cable 0,6 mm Number of wire pairs max	10 Pieces
Control and signal cable 0,8 mm Number of wire pairs min	6 Pieces
Control and signal cable 0,8 mm Number of wire pairs max	6 Pieces

Logistics data

Article name	M 0 GG
Article number	353703
Delivery scope	Fill and air-release funnel
	Hydrolysis resistance PUR cast resin GG
	Packed in practical and easy-to-use two-chamber bags
	Transparent plastic shell
	PVC insulation tape
	Protective gloves
	Assembly instructions
Shelf life	24 Month
Storage temperatur max	35 °C
Storage temperatur min	15 °C
Country of origin	Germany
Customs tariff number	39095090
EAN/GTIN	4010311171005

Packaging data

Alternative unit of measure	Case	Pal. OW
Base quantity	1	480
Base unit of measure	Piece	Piece
Lenght (mm)	210	1200
Width (mm)	157	800
Height (mm)	55	1130
Net weight (kg)	0.381	182.88
Gross weight (kg)	0.381	201.08