

3-core straight-through joint  
for armoured 3-core polymeric cables up to 7.2 kV

Straight-through joints M...MS6 are suitable for armoured 3-core polymericinsulated cables (PVC, PE, XLPE, EPR) without an outer semi-conductive layer. UG cast resin ensure flame protection (e.g. for mining).




Product description

Article name	M4 B-MS6
Article number	124359
Notes	The European Commission amended Annex XVII of the REACH Regulation (EC) (new number 74) with Regulation (EU) 2020/1149, which entered into force on 24 August 2020. In accordance with the new REACH Regulation, appropriate training will be required prior to the industrial or professional use of diisocyanates, adhesives and sealants as of 24 August 2023. All information regarding training materials and training courses is available on the ISOPA/ALIPA website <a href="https://www.safeusediisocyanates.eu/">https://www.safeusediisocyanates.eu/</a>
Optional accessory	Connectors (see Connecting technology)

Characteristics
Resistant to chemical agents
Longitudinally and transversely watertight
High mechanical strength
Quick, safe and easy assembly

Applications
Indoor
Outdoor
Underground
Water
Installation ducts

## Technical data



Article name	M4 B-MS6
Article number	124359
Voltage levels	U0/U (Um) 3,6/6 (7,2) kV - 3,8/6,6 (7,2) kV
Length L1	432 mm
Length L2	384 mm
Diameter D1	29 mm
Diameter D2	52 mm
Diameter D3	90 mm
Nominal cross section Polymeric cable armoured with concentric conductor min	25 mm <sup>2</sup>
Nominal cross section Polymeric cable armoured with concentric conductor max	50 mm <sup>2</sup>
Nominal cross section Polymeric cable armoured min	25 mm <sup>2</sup>
Nominal cross section Polymeric cable armoured max	70 mm <sup>2</sup>
Diameter cable min	29 mm
Diameter cable max	55 mm

## Logistics data

Article name	M4 B-MS6
Article number	124359
Delivery scope	Spacer sleeve
	Hydrolysis resistance PUR type UG cast resin
	Packed in practical and easy-to-use two-chamber bags
	Transparent plastic shell
	Copper braid tube
	Fill and air-release funnel
	PVC insulation tape
	Protective gloves
	Assembly instructions
Shelf life	24 Month
Country of origin	Germany
Customs tariff number	39095090
EAN/GTIN	4010311015231

## Packaging data

Packaging type	Carton	Pal. EU
Content quantity	1	30
Unit of measure	Piece	Piece
Length (mm)	488	1200
Width (mm)	248	800
Height (mm)	195	1130
Net weight (kg)	3.597	107.91
Gross weight (kg)	3.597	136.91