

Cast resin straight-through joint

with screw connectors for polymeric cables

Universally suitable for connecting polymeric cables or conductors insulated with PVC, PE, XLPE and EPR (e.g. N(A)YY, NYM, TT). With hydrolysis resistance PUR cast resin EG. With screw connectors, suitable for aluminium or copper conductors.



Product description

Article name	M 11 V
Article number	131863
Notes	The European Commission amended Annex XVII of the REACH Regulation (EC) (new number 74) with Regulation (EU) 2020/1149, which entered into force on 24 August 2020. In accordance with the new REACH Regulation, appropriate training will be required prior to the industrial or professional use of diisocyanates, adhesives and sealants as of 24 August 2023. All information regarding training materials and training courses is available on the ISOPA/ALIPA website https://www.safeusediisocyanates.eu/
Optional accessory	Cleaner UNIVERSAL CLEANER 121 (see Accessories)


Characteristics

Compact dimensions
Splice area visible before casting
High-quality transparent shockproof plastic shell
Resistant to chemical agents
Stabilized against UV rays
Resistant to alkaline earth elements
Longitudinally and transversely watertight
High electrical insulating values
High mechanical strength
Ready for immediate operation
Quick, safe and easy assembly
Large filler aperture to facilitate casting

Applications

Indoor
Outdoor
Underground
Water
Installation ducts

Technical data



Article name	M 11 V
Article number	131863
Voltage levels	U0/U (Um) 0,6/1 (1,2) kV
Test standards	EN 50393
Length L	190 mm
Height H	50 mm
Diameter D	36 mm
Nominal cross section Polymeric cable unarmoured per conductor 3x min	2 mm ²
Nominal cross section Polymeric cable unarmoured per conductor 3x max	6 mm ²
Nominal cross section Polymeric cable unarmoured per conductor 4x min	1.5 mm ²
Nominal cross section Polymeric cable unarmoured per conductor 4x max	6 mm ²
Nominal cross section Polymeric cable unarmoured per conductor 5x min	1.5 mm ²
Nominal cross section Polymeric cable unarmoured per conductor 5x max	6 mm ²
Diameter cable max	26 mm
Nominal cross section Polymeric cable with concentric conductor per conductor 3x min	1.5 mm ²
Nominal cross section Polymeric cable with concentric conductor per conductor 3x max	6 mm ²
Nominal cross section Polymeric cable with concentric conductor per conductor 4x min	1.5 mm ²
Nominal cross section Polymeric cable with concentric conductor per conductor 4x max	6 mm ²

Logistics data

Article name	M 11 V
Article number	131863
Delivery scope	Cover
	Hydrolysis resistance PUR cast resin EG
	Packed in practical and easy-to-use two-chamber bags
	Transparent plastic shell
	PVC insulation tape
	Protective gloves
	Screw connector
	Spacers
	Assembly instructions
Shelf life	40 Month
Storage temperatur max	35 °C
Storage temperatur min	15 °C
Country of origin	Germany
Customs tariff number	39095090
EAN/GTIN	4010311020327

Packaging data

Packaging type	Case	Pal. OW
Content quantity	1	480
Unit of measure	Piece	Piece
Lenght (mm)	207	1200
Width (mm)	158	800
Height (mm)	47	1130
Net weight (kg)	0.439	210.72
Gross weight (kg)	0.439	228.92