

## Cooling spray

for thermal fault diagnosis

Ensures rapid and reliable cooling down to  $-50^{\circ}\text{C}$ , flammable, evaporates immediately and without residue, particularly material-compatible, ideal cooling source for standard applications.



## Product description

Article name	MINUS Spray
Article number	124044

### Characteristics

Cools down to $-50^{\circ}\text{C}$
Does not damage construction materials
Fast and reliable

### Applications

Thermal fault detection
Prevention of overheating during soldering
Cooling of heat-sensitive components
Effective overriding of thermal switches and thermostats etc.

## Technical data

Article name	MINUS Spray
Article number	124044
Content	0.4 l
Colours	transparent color
Density	0.55 g/cm <sup>3</sup>

## Logistics data

Article name	MINUS Spray
Article number	124044
Delivery scope	Cooling spray
Shelf life	24 Month
Storage temperatur max	25 °C
Storage temperatur min	20 °C
Country of origin	Germany
Customs tariff number	27111397
EAN/GTIN	4010311048987

## Packaging data

Packaging type	Tin	Case	Carton	Pal. OW
Content quantity	1	3	12	1008
Unit of measure	Piece	Piece	Piece	Piece
Lenght (mm)	67	245	280	1200
Width (mm)	67	225	220	800
Height (mm)	197	88	210	1400
Net weight (kg)	0.309	0.927	3.708	311.472
Gross weight (kg)	0.309	1.227	4.008	329.672