

Cooling spray
for thermal fault diagnosis

Ensures rapid and reliable cooling down to -50° C,
flammable, evaporates immediately and without
residue, particularly material-compatible, ideal cooling
source for standard applications.



Product description

Article name	MINUS Spray
Article number	124044

Characteristics

- Cools down to -50 °C
- Does not damage construction materials
- Fast and reliable

Applications

- Thermal fault detection
- Prevention of overheating during soldering
- Cooling of heat-sensitive components
- Effective overriding of thermal switches and thermostats etc.

Technical data

Article name	MINUS Spray
Article number	124044
Content	0.4 l
Colours	transparent color
Density	0.55 g/cm ³

Logistics data

Article name	MINUS Spray
Article number	124044
Delivery scope	Cooling spray
Shelf life	24 Month
Storage temperatur max	25 °C
Storage temperatur min	20 °C
Country of origin	Germany
Customs tariff number	27111397
EAN/GTIN	4010311048987

Packaging data

Alternative unit of measure	Tin	Carton	Pal. OW
Base quantity	1	12	1008
Base unit of measure	Piece	Piece	Piece
Lenght (mm)	67	280	1200
Width (mm)	67	220	800
Height (mm)	197	210	1400
Net weight (kg)	0.309	3.708	311.472
Gross weight (kg)	0.309	4.008	329.672