


PVC insulation tape thin  
for marking bundling and insulating

High-quality, flexible, UV-resistant PVC insulation tape  
for the electrical and telecommunications sector.



Product description

|                |                       |
|----------------|-----------------------|
| Article name   | No. 128 blue/RAL 5015 |
| Article number | 145810                |

|  |
|--|
| Characteristics  |
| Synthetic rubber adhesive                                |
| Very good resistance to abrasion, corrosion and moisture |
| Stabilized against UV rays                               |
| High flexibility   |
| Withstands high electrical stresses                      |
| Good adhesive properties                                 |
| Easy processing  |
| Oil-resistant  |
| Resistant to dilute acids and alkalis                    |

|  |
|--|
| Applications   |
| Sealing  |
| Padding of cable insulation                              |
| Bundling   |
| Reinforcing  |
| As insulation of electrical and telecommunication cables |
| Colour-coding  |

## Technical data

|   |                       |
|---|-----------------------|
| Article name                                    | No. 128 blue/RAL 5015 |
| Article number                                  | 145810                |
| Test standards                                  | IEC 60454-3-1-5       |
| Materials                                       | PVC                   |
| Length L  | 10 m                  |
| Width B   | 19 mm                 |
| Thickness                                       | 0.15 mm               |
| Colours   | blue                  |
| Adhesive strength                               | 1.8 N/cm              |
| Adhesive strength (associated standard)         | IEC 60454-2           |
| Elongation at break                             | 170 %                 |
| Elongation at break (associated standard)       | IEC 60454-2           |
| Tensile strength at break                       | 30 N/cm               |
| Tensile strength at break (associated standard) | IEC 60454-2           |
| Unwinding force                                 | 1.8 N/cm              |
| Unwinding force (associated standard)           | IEC 60454-2           |
| Operation temperature min                       | 0 °C                  |
| Operation temperature max                       | 90 °C                 |
| Operation temperature (associated standard)     | IEC 60454-2           |
| Dielectric strength                             | 40 kV/mm              |
| Dielectric strength (associated standard)       | IEC 60454-2           |

## Logistics data

|                        |                       |
|------------------------|-----------------------|
| Article name           | No. 128 blue/RAL 5015 |
| Article number         | 145810                |
| Delivery scope         | PVC insulation tape   |
| Shelf life             | 24 Month              |
| Storage temperatur max | 25 °C                 |
| Storage temperatur min | 10 °C                 |
| Country of origin      | Italy                 |
| Customs tariff number  | 39191012              |
| EAN/GTIN               | 4010311013732         |

## Packaging data

| Packaging type    | Roll  | Bundle | Carton |
|-------------------|-------|--------|--------|
| Content quantity  | 1     | 10     | 200    |
| Unit of measure   | Piece | Piece  | Piece  |
| Lenght (mm)       | 67    | 67     | 305    |
| Width (mm)        | 67    | 67     | 240    |
| Height (mm)       | 20.5  | 205    | 225    |
| Net weight (kg)   | 0.036 | 0.36   | 7.2    |
| Gross weight (kg) | 0.036 | 0.365  | 7.5    |