

PVC insulation tape thin
for marking bundling and insulating

High-quality, flexible, UV-resistant PVC insulation tape
for the electrical and telecommunications sector.



Product description

Article name	No. 128 orange/RAL 2009
Article number	145822

Characteristics	Applications
Synthetic rubber adhesive	Sealing
Very good resistance to abrasion, corrosion and moisture	Padding of cable insulation
Stabilized against UV rays	Bundling
High flexibility	Reinforcing
Withstands high electrical stresses	As insulation of electrical and telecommunication cables
Good adhesive properties	Colour-coding
Easy processing	
Oil-resistant	
Resistant to dilute acids and alkalis	

Technical data

Article name	No. 128 orange/RAL 2009
Article number	145822
Test standards	IEC 60454-3-1-5
Materials	PVC
Length L	10 m
Width B	15 mm
Thickness	0.15 mm
Colours	orange
Adhesive strength	1.8 N/cm
Adhesive strength (associated standard)	IEC 60454-2
Elongation at break	170 %
Elongation at break (associated standard)	IEC 60454-2
Tensile strength at break	30 N/cm
Tensile strength at break (associated standard)	IEC 60454-2
Unwinding force	1.8 N/cm
Unwinding force (associated standard)	IEC 60454-2
Operation temperature min	0 °C
Operation temperature max	90 °C
Operation temperature (associated standard)	IEC 60454-2
Dielectric strength	40 kV/mm
Dielectric strength (associated standard)	IEC 60454-2

Logistics data

Article name	No. 128 orange/RAL 2009
Article number	145822
Delivery scope	PVC insulation tape
Shelf life	24 Month
Storage temperatur max	25 °C
Storage temperatur min	10 °C
Country of origin	Italy
Customs tariff number	39191012
EAN/GTIN	4010311018683

Packaging data

Packaging type	Roll	Bundle	Carton
Content quantity	1	10	200
Unit of measure	Piece	Piece	Piece
Lenght (mm)	66	66	290
Width (mm)	66	66	235
Height (mm)	16.7	167	180
Net weight (kg)	0.028	0.28	5.6
Gross weight (kg)	0.028	0.285	5.9