

PVC insulation tape
for marking bundling and insulating

Elastic, UV-resistant PVC insulating tape



Product description

Article name	No. 228 transparent color
Article number	364756

Characteristics
Synthetic rubber adhesive
Moisture-resistant
Oil-resistant
Resistant to dilute acids and alkalis
Stabilized against UV rays
High flexibility
Good adhesive properties
Easy processing

Applications
Sealing
Padding of cable insulation
Bundling
Reinforcing
As insulation of electrical and telecommunication cables
Marking of insulation with high mechanical tension requirements

Technical data

Article name	No. 228 transparent color
Article number	364756
Materials	PVC
Length L	10 m
Width B	50 mm
Thickness	0.19 mm
Colours	transparent color
Elongation at break	300 %
Elongation at break (associated standard)	IEC 60454-2
Tensile strength at break	35 N/cm
Tensile strength at break (associated standard)	IEC 60454-2
Unwinding force	3.5 N/cm
Unwinding force (associated standard)	IEC 60454-2
Adhesion to steel	2 N/cm
Adhesion to steel (associated standard)	IEC 60454-2
Adhesion to surfaces	2.4 N/cm
Adhesion to surfaces (associated standard)	IEC 60454-2
Flammability	self-extinguishing
Flammability (associated standard)	IEC 60454-2
Elastic modulus to 35%	3.5 MPa
Elastic modulus to 35% (associated standard)	IEC 60454-2
Operation temperature min.	-18 °C
Operation temperature max.	105 °C
Operation temperature (associated standard)	IEC 60454-2
Dielectric strength	45 kV/mm
Dielectric strength (associated standard)	IEC 60454-2

Logistics data

Article name	No. 228 transparent color
Article number	364756
Delivery scope	PVC insulation tape
Shelf life	24 Month
Storage temperatur max	25 °C
Storage temperatur min	5 °C
Country of origin	Belgium
Customs tariff number	39191012
EAN/GTIN	4010311189017

Packaging data

Packaging type	Roll	Carton
Content quantity	1	100
Unit of measure	Piece	Piece
Lenght (mm)	62	330
Width (mm)	62	265
Height (mm)	50	275
Net weight (kg)	0.123	12.3
Gross weight (kg)	0.123	12.6