

Sealing tape
for permanently flexible sealing

Universally suitable, auto-amalgamating, to seal homogeneously or upholstering cables and conductors.



Product description

Article name	No. 64
Article number	125591

Characteristics
Self-amalgamating
Corrosion-resistant
Ozone-resistant
Permanently flexible
Excellent adherence to metal, glass rubber and plastic
Superior physical properties

Applications
Sealing of cable and conductor interstices
Repairing of damaged cable sheaths
Water-resistant sealing of cable entry points
Padding of cable insulation
Suitable for connections using acrylic and epoxy resin compounds
Protection against dust, moisture and corrosion

Technical data

Article name	No. 64
Article number	125591
Materials	Butyl-/Rubber based
Length L	1.5 m
Width B	38 mm
Thickness	3.2 mm
Colours	black
Tensile strength at break	0.1 MPa
Heat resistance min	-30 °C
Heat resistance max	80 °C
Specific volume resistivity	$10^{12} \Omega \text{ cm}$
Dielectric strength	23 kV/mm

Logistics data

Article name	No. 64
Article number	125591
Delivery scope	Sealing tape
Country of origin	France
Customs tariff number	40051000
EAN/GTIN	4010311005584

Packaging data

Alternative unit of measure	Tin	Carton
Base quantity	1	32
Base unit of measure	Piece	Piece
Lenght (mm)	93	551
Width (mm)	90	250
Height (mm)	50	240
Net weight (kg)	0.343	10.976
Gross weight (kg)	0.343	11.276