

Cast resin branch joint

with strain relief for polymeric cables and mass-impreg. paper cables

Universally suitable for branching polymeric cables insulated with PVC, PE, XLPE and paper (e.g. N(A)YY, N(A)KBA, GN-CLN, TT) with or without concentric conductor and mass-impregnated paper cables. With hydrolysis resistance PUR cast resin GG. Suitable for branch clamps on copper and aluminium conductors.




Product description

Article name	P 3 GG
Article number	329589
Optional accessory	For size 2...4 branch clamp KP (see Connecting technology)
	For size 5...7 branch clamp HE 1/70/150 (see Connecting technology)
	Cleaner UNIVERSAL CLEANER 121 (see Accessories)

Characteristics
Compact design
Integrated strain relief
High-quality brown shockproof plastic shell
Resistant to chemical agents
Stabilized against UV rays
Resistant to alkaline earth elements
Longitudinally and transversely watertight
High electrical insulating values
High mechanical strength
Ready for immediate operation
Quick, safe and easy assembly
Large filler aperture to facilitate casting
Integrated strain relief

Applications
Indoor
Outdoor
Underground
Water
Installation ducts

Technical data



Article name	P 3 GG
Article number	329589
Voltage levels	U0/U (Um) 0,6/1 (1,2) kV
Test standards	EN 50393
Length L	342 mm
Height H	160 mm
Diameter D	90 mm
Diameter cable Main cable min	15 mm
Diameter cable Main cable max	35 mm
Diameter cable Branch cable min	12 mm
Diameter cable Branch cable max	30 mm
Nominal cross section Main cable Mass-impregnated paper cable per conductor 3x min	10 mm ²
Nominal cross section Main cable Mass-impregnated paper cable per conductor 3x max	16 mm ²
Nominal cross section Main cable Mass-impregnated paper cable per conductor 4x min	10 mm ²
Nominal cross section Main cable Mass-impregnated paper cable per conductor 4x max	16 mm ²
Nominal cross section Main cable Polymeric cable unarmoured per conductor 4x min	10 mm ²
Nominal cross section Main cable Polymeric cable unarmoured per conductor 4x max	25 mm ²
Nominal cross section Branch cable Polymeric cable unarmoured per conductor 4x min	4 mm ²
Nominal cross section Branch cable Polymeric cable unarmoured per conductor 4x max	16 mm ²
Nominal cross section Main cable Polymeric cable with concentric conductor per conductor 3x min	10 mm ²
Nominal cross section Main cable Polymeric cable with concentric conductor per conductor 3x max	16 mm ²
Nominal cross section Main cable Polymeric cable with concentric conductor per conductor 4x min	10 mm ²
Nominal cross section Main cable Polymeric cable with concentric conductor per conductor 4x max	16 mm ²
Nominal cross section Branch cable Polymeric cable with concentric conductor per conductor 4x min	4 mm ²

Nominal cross section Branch cable Polymeric cable with concentric conductor per conductor 16 mm²
4x max

Logistics data

Article name	P 3 GG
Article number	329589
Delivery scope	Sealing gaskets
	Hydrolysis resistance PUR cast resin GG
	Packed in practical and easy-to-use two-chamber bags
	Plastic shell with integrated strain relief
	Hexagon head screws and nuts
	Assembly instructions
Shelf life	24 Month
Country of origin	Germany
Customs tariff number	39095090
EAN/GTIN	4010311162737

Packaging data

Alternative unit of measure	Case	Pal. EU
Base quantity	1	50
Base unit of measure	Piece	Piece
Length (mm)	366	1200
Width (mm)	226	800
Height (mm)	177	1130
Net weight (kg)	3.693	184.65
Gross weight (kg)	3.693	213.65