

Cross-section reducing
for joints

Kit for reducing the cross-section for medium voltage
mass-impregnated paper cables.



Product description

| | |
|----------------|---------------|
| Article name | PS (H) 95-240 |
| Article number | 197692 |

| |
|-------------------------------|
| Characteristics |
| Quick, safe and easy assembly |
| Ready for immediate operation |

| |
|--------------------|
| Applications |
| Indoor |
| Outdoor |
| Underground |
| Ductwork |
| Installation ducts |

Technical data

| | |
|---|---|
| Article name | PS (H) 95-240 |
| Article number | 197692 |
| Selection Note | U0/U (Um) 12/20 (24) kV - 12,7/22 (24) kV |
| Applicable for | CHMP(H)3, CHMP(H)3-1 |
| Diameter over core insulation after removal of the outer conductive layer min | 19.9 mm |
| Nominal cross section 24 kV min | 95 mm ² |
| Nominal cross section 24 kV max | 240 mm ² |
| Nominal cross section paper insulated cable min | 35 mm ² |
| Nominal cross section paper insulated cable max | 70 mm ² |

Logistics data

| | |
|-----------------------|-----------------------|
| Article name | PS (H) 95-240 |
| Article number | 197692 |
| Delivery scope | Heat shrinkable tubes |
| | Oil barrier tubing |
| | Mastic tape |
| Country of origin | Germany |
| Customs tariff number | 39269097 |
| EAN/GTIN | 4010311052274 |

Packaging data

| | |
|-----------------------------|-------|
| Alternative unit of measure | Bag1 |
| Base quantity | 1 |
| Base unit of measure | Piece |
| Length (mm) | 500 |
| Width (mm) | 250 |
| Height (mm) | 100 |
| Net weight (kg) | 0.367 |
| Gross weight (kg) | 0.367 |