

Cross-section reducing
for joints

Kit for reducing the cross-section for medium voltage
mass-impregnated paper cables.



Product description

Article name	PS (VM) 95-240
Article number	298442

Characteristics
Quick, safe and easy assembly
Ready for immediate operation

Applications
Indoor
Outdoor
Underground
Ductwork
Installation ducts

Technical data

Article name	PS (VM) 95-240
Article number	298442
Selection Note	U0/U (Um) 6/10 (12) kV - 8,7/15 (17,5) kV
Applicable for	CHMPRSV 3-1 (VM)
Diameter over core insulation after removal of the outer conductive layer min	17.3 mm
Nominal cross section 12 kV min	95 mm ²
Nominal cross section 12 kV max	240 mm ²
Nominal cross section 17,5 kV min	95 mm ²
Nominal cross section 17,5 kV max	240 mm ²
Nominal cross section paper insulated cable min	35 mm ²
Nominal cross section paper insulated cable max	70 mm ²

Logistics data

Article name	PS (VM) 95-240
Article number	298442
Delivery scope	Heat shrinkable tubes
	Oil barrier tubing
	Mastic tape
Country of origin	Germany
Customs tariff number	39269097
EAN/GTIN	4010311154336

Packaging data

Alternative unit of measure	Bag1
Base quantity	1
Base unit of measure	Piece
Length (mm)	500
Width (mm)	250
Height (mm)	100
Net weight (kg)	1.309
Gross weight (kg)	1.309