

## Clear varnish

for insulation and sealing

Contains a high-quality acrylic resin lacquer, protects against acids, alkalis, alcohols, moisture and adverse environmental influences, does not drip, solderable. Effective from -70° C to +120° C. Adheres to metal, plastic, wood, cardboard, glass etc.



## Product description

Article name	PLASTIC Spray
Article number	124049

Characteristics  
Highly resistant

Applications  
Sealing

Elimination or prevention of current leakage, corona discharges, soft short circuits

Insulation of panel boards, components, wires and cables

Protective film against pollutants such as acid, alkali, alcohol and moisture

## Technical data

Article name	PLASTIC Spray
Article number	124049
Content	0.4 l
Colours	transparent color
Drying time	20 minutes
Flash point	-97 °C
Density	0.78 g/cm <sup>3</sup>
Heat resistance min	-70 °C
Heat resistance max	120 °C
Dielectric strength	21 kV/mm

## Logistics data

Article name	PLASTIC Spray
Article number	124049
Delivery scope	Clear varnish
Shelf life	24 Month
Storage temperatur max	25 °C
Storage temperatur min	20 °C
Country of origin	France
Customs tariff number	32082010
EAN/GTIN	4010311057286

## Packaging data

Alternative unit of measure	Tin	Carton	Pal. EU
Base quantity	1	12	900
Base unit of measure	Piece	Piece	Piece
Lenght (mm)	65	270	1200
Width (mm)	65	202	800
Height (mm)	200	203	1400
Net weight (kg)	0.389	4.668	350.1
Gross weight (kg)	0.389	4.968	379.1